

Supermicro SuperChassis SC113MFAC2-R606CB 1U 8xSFF RED PSU

Kod producenta: CSE-113MFAC2-R606CB



Chassis Form Factor	Rack 1U
# of 2.5 hot-swap bays	8
Power Supply	Redundant
PSU Wattage	600W
PSU Certification	80+ Platinum
Chassis Dimensions	437 x 43 x 507mm
Uwagi	SAS3 12Gb/s Hybrid backplane

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-113MFAC2-R606CB • SuperChassis 113MFAC2-R606CB (Black)

Form Factor

1U chassis for motherboard support size of ATX 12" x 10"

Processor Support

Dual and Single Intel® and AMD processors

Dimensions

- Height • 1.7" (43mm)
- Width • 17.2" (437mm)
- Depth • 19.98" (507mm)
- Packaging • 24" (W) x 8.3"(H) 30" (L)
- Gross Weight • 33 lb (14.97 kg)
- Available Colors • black

Expansion Slots

1 full-height & full-length expansion slot(s)

Peripheral Drives

1 x Optional slim DVD-ROM drive bay

Drive Bays

Hot-swap 8 x 2.5" hot-swap SAS/SATA drive bay

Front Panel

- Buttons**
 - Power On/Off button
 - System Reset Button
- LEDs**
 - 2 Network Activity LEDs
 - HDD activity LED
 - Power Status LED
 - Unit Identification (UID) LED

Motherboard (for CSE-113MFAC2-R606CB)

- | | |
|------------------------------|-----------------------------|
| X10DRL-C | X10DRL-CT |
| X10DRL-iT | X10SRH-CF |
| X10SRH-CLN4F | X10SRM-F |
| X10SRM-TF | X11SSH-CTF |
| X11SSH-F | X11SSH-LN4F |
| X11SSH-TF | X11SSi-LN4F |
| X11SSL | X11SSL-CF |
| X11SSL-F | X11SSL-nF |
| X11SSM | X11SSM-F |

Server(s) for SC113MFAC2-R606CB

[1028R-MCTR](#)

System Cooling

Fans 4x 40x28mm PWM fan
2x fans for AOC cooling

System Monitoring

Chassis intrusion switch

Operating Environment (System)

- Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range
- Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range
- Operating Relative Humidity • 8% ~ 90% (non-condensing)
Range
- Non-Operating Relative Humidity • 5% - 95% (non-condensing)
Range

Power Supply with Power Distributor

600W Redundant High-Efficiency Power Supplies w/Power Distributor, PMBus 1.2, I²C, and PFC

AC Input • 100-240V, 50-60Hz, 7.5-3.0A

DC Output • +5V standby: 3A
• +12V: 50A

Certification 
Platinum Certified
[\[Test Report \]](#)

Regulatory (Power Supply)

- Power Supply Safety / EMC
- USA - UL listed, FCC
 - Canada - CUL listed
 - Germany - TUV Certified
 - Europe/CE Mark
 - EN 60950/IEC 60950-Compliant

Strona firmowa produktu:

<https://www.supersstorage.pl/supermicro-superschassis-sc113mfac2-r606cb-1u-8-bay-hot-swap-psu-s-2209.html>
Copyright © 2024 www.supersstorage.pl | plater, 20 kwiecień 2024 Strona 2713

