

Supermicro SuperChassis SC119TQ-R700UB 1U 8xSFF RED PSU

Kod producenta: CSE-119TQ-R700UB



Chassis Form Factor	Rack 1U
# of 2.5 hot-swap bays	8
Power Supply	Redundant
PSU Wattage	750W
PSU Certification	80+ Gold

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-119TQ-R700UB • SuperChassis 119TQ-R700UB (Black)

Form Factor

1U chassis optimized for 12.8" x 16.5" proprietary motherboard

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

- Height • 1.7" (43mm)
- Width • 17.2" (437mm)
- Packaging • 24" x 7.9" x 35.1" (608mm x 200mm x 891mm)
- Depth • 26.6" (676mm)
- Gross Weight • 42 lbs (19 kg)
- Available Colors • Black

Expansion Slots

- 2x Full-height expansion slots
- 1x Low-profile AOC slot

Drive Bays

- 8x 2.5" SAS / SATA Hot-swap drive bays
- Hot-swap • SAS or enterprise SATA HDD only recommended

SAS / SATA Backplane

1x 1U SAS / SATA backplane

Peripheral Drives

- DVD-ROM • Slim DVD-ROM drive (optional)

Front Panel

- Buttons
 - Power On/Off Button
 - System Reset Button
 - UID Button
- LEDs
 - Power LED
 - Hard drive activity LED
 - 2x Network activity LEDs
 - Universal Information (UID) LED

Motherboard (for CSE-119TQ-R700UB)

- [H8DGU-LN4F+](#)
- [X8DTU-6F+](#)
- [X8DTU-6F+-LR](#)
- [X8DTU-6TF+](#)
- [X8DTU-6TF+-LR](#)
- [X8DTU-LN4F+](#)
- [X8DTU-LN4F+-LR](#)

Server(s) for SC119TQ-R700UB

- [1026T-URF4+-LR](#)
- [1026T-URF4+](#)
- [1026T-6RF+](#)
- [1026T-6RFT+-LR](#)
- [1026T-6RF+-LR](#)
- [1026T-6RFT+](#)

System Cooling

- Fans • 5x 4cm Counter-rotating fans

Operating Environment (System)

- Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F) Range
- Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F) Range
- Operating Relative Humidity • 8% ~ 90% (non-condensing) Range
- Non-Operating Relative Humidity • 5% - 95% (non-condensing) Range

Power Supply

- 700W/750W Redundant AC-DC high-efficiency power supply with PMBus and I2C
 - 700W: 100-140 V, 50-60 Hz, 8.5-6 Amp
- AC Input
 - 750W: 180-240 V, 60-50 Hz, 5-3.8 Amp
- DC Output +5V standby
 - 3 Amp
- DC Output +12V
 - 700W: 58 Amp @ 100-140V
 - 750W: 62 Amp @ 180-240V
- With Power Distributor
 - +5V: 25 Amp
 - +3.3V: 25 Amp
 - -12V: 0.6 Amp

Certification



[Gold Certified](#)

Regulatory (Power Supply)

- USA - UL listed, FCC
- Canada - CUL listed
- Power Supply • China - CCC Mark
- Safety / EMC • Europe/CE Mark
- EN 60950/IEC 60950-Compliant

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc119tq-r700ub-1u-8xsff-red-psu-p-2229.html>