Supermicro SuperChassis SC119TQ-R700WB 1U 8xSFF RED PSU

Kod producenta: CSE-119TQ-R700WB



Chassis Form Factor	Rack 1U
# of 2.5 hot-swap bays	8
Power Supply	Redundant
PSU Wattage	750W
PSU Certification	80+ Gold

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-119TQ-R700WB	• SuperChassis 119TQ-R700WB (**Black**)

Form Factor

- 1U chassis supports max. motherboard size: 12.8" x 16.5" (proprietary)
- Optimized for WIO (W series) motherboards

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height	• 1.7" (43mm)
Width	• 17.2" (437mm)
Depth	• 26.6" (676mm)
Packaging	• 24" x 7.9" x 35.1" (608mm x 200mm x 891mm)
Gross Weight	• 42 lbs (19 kg)
Available Colors	• Black

Expansion Slots

- 2x Full-height Expansion Slots (Riser Card Required)
- 1x Low-profile Expansion Slot (Riser Card Required)

Drive Bays

Hot-swap	• 8x 2.5" SAS / SATA Hot-swap drive bays • SAS or enterprise SATA HDD only recommended

SAS / SATA Backplane

1x 1U SAS / SATA backplane

Peripheral Drives

DVD-ROM	• Slim DVD-ROM drive (optional)

Front Panel

Buttons	• Power On/Off Button • System Reset Button • UID Button
LEDs	• Power LED • Hard drive activity LED • 2x Network activity LEDs • Universal Information LED

Motherboard (for CSE-119TQ-R700WB)

X9DRW-3LN4F+ X9DRW-3TF+
X9DRW-7TPF+ X9DRW-iTPF
X9DRW-iTPF+

Server(s) for SC119TQ-R700WB

1027R-WTRFTP 1027R-72RFTP
1027R-WRF4+ 1027R-WRFT+

System Cooling

Fans	• 5x 4cm Counter-rotating PWM fans

Operating Environment (System)

Operating Temperature Range	• 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range	• -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range	• 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range	• 5% - 95% (non-condensing)

Power Supply

700W/750W Redundant AC-DC high-efficiency power supply with PMBus and I2C

AC Input	• 700W: 100-140 V, 50-60 Hz, 8.5-6 Amp • 750W: 180-240 V, 60-50 Hz, 5-3.8 Amp
DC Output +5V standby	• 3 Amp
DC Output +12V	• 700W: 58 Amp @ 100-140V • 750W: 62 Amp @ 180-240V
With Power Distributor	• +5V: 25 Amp • +3.3V: 25 Amp • -12V: 0.6 Amp
Certification	80 PLUS GOLD **Gold Certified**

Regulatory (Power Supply)

Power Supply Safety / EMC	• USA - UL listed, FCC • Canada - CUL listed • China - CCC Mark • Europe/CE Mark • EN 60950/IEC 60950-Compliant • Germany - TUV Certified

Strona firmowa produktu:
https://www.superstorage.pl/supermicro-superchassis-sc119tq-r700wb-1u-8xsff-red-psu-p-2230.html