Emulex HBA 8Gb/s Fibre Channel Single Port PCI-Express Adapter (LPE12000-M8)

Kod producenta: LPE12000-M8



Ilość portów 1

Przepustowość 8Gb/s Złacza zew. 1x LC

Typ złącza magistrali PCI Express 2.0 x8

Format Low Profile
Gwarancja 36 m-cy

Unparalleled manageability, reliability, performance and ease of deployment

Streamlined installation and management, unrivaled scalability and industry-leading virtualization support make the single-port LPe12000 Fibre Channel Host Bus Adapter (HBA) an ideal solution for enterprise, mixed-operating system (OS) and virtual server environments. With powerful management capabilities and broad platform support, they deliver maximum performance in the broadest range of applications and environments.

Proven design, architecture and interface

Emulex HBAs feature ahighly integrated processor design with minimized onboard components to improve host performance and efficiency. Advanced error-checking features ensure the integrity of block data as it traverses the Storage Area Network (SAN). The firmware-based architecture enables feature and performance upgrades without costly hardware changes. The unique Service Level Interface ($SLI^{\text{\tiny IM}}$) allows use of a common driver across all models of Emulex HBAs on a given OS platform. Installation and management facilities are designed to minimize server reboots and further simplify deployment.

Key Features

- PCIe 2.0 bus-compliant, with PCIe 1.0 backward compatibility supported
- Support for Message Signaled Interrupts eXtended (MSI-X), improves host utilization & enhances application performance
- Support for 8Gbps, 4Gbps and 2Gbps Fibre Channel devices
- ullet Comprehensive virtualization capabilities with support for N_Port ID Virtualization (NPIV) and Virtual Fabric
- Host-to-Fabric FG-SP ignther to 2024 www.superstorage.pl | piątek, 19 kwiecień 2024 Strona: 1 / 2

- T10 Protection Information (T10 PI) ready ensures end-to-end data integrity
- Common driver model allows a single driver to support all Emulex HBAs on a given OS
- Easy deployment of new firmware with minimal server reboots
- Efficient centralized administration of Emulex HBAs via powerful management tools

Key Benefits

- Provides superior performance for the enterprise
- Integrates seamlessly into existing SANs
- Supports IT server consolidation and energy conservation initiatives
- Allows application of SAN best practices, tools and processes with virtual server deployments
- Assures data availability and data integrity
- Improves IT staff productivity through simplified deployment and management

Performance Features

- Doubling the maximum Fibre Channel link rate from 4Gbps to 8Gbps and enhanced virtualization capabilities help support IT "Green" initiatives
- Frame-level multiplexing and out-of-order frame reassembly increases link efficiency and maximizes HBA performance.

Data Protection Features

- End-to-end data protection with hardware parity, CRC, ECC and other advanced error-checking and correcting algorithms ensure data is safe from corruption.
- Only Emulex HBAs provide end-to-end data integrity with support of the T10 Protection Information (T10-PI) standard to prevent silent data corruption and help ensure the integrity of user data as it is transferred from the application to the SAN.

Deployment and Management Features

- Universal boot capability allows the appropriate boot environment to be automatically selected for any given hardware.
- Boot-from-SAN capability reduces system management costs and increases uptime.
- Detailed real-time event logging and tracing enables guick diagnosis of SAN problems.
- Beaconing feature flashes the HBA LEDs, simplifying their identification within server racks.
- Environmental monitoring feature helps to optimize SAN availability.
- LightPulse® LPe12000/LPe12002

Strona firmowa produktu:

https://www.superstorage.pl/emulex-hba-8gbs-fibre-channel-single-port-pci-express-adapter-lpe12000-m8-p-2482.html

Strona: 2 / 2