

Supermicro MBD-X11SSH-LN4F, Single SKT, Intel C236 Chipset, SATA, 4xGbE, IPMI,M.2 Bulk

Kod producenta: MBD-X11SSH-LN4F-B



Category	Server
Form Factor	Micro-ATX
Dimensions	9.6" x 9.6"
CPU Socket	LGA 1151 (Socket H4)
# of CPU sockets	1
Supported CPU's	Intel Xeon E3-1200v5
Chipset	Intel C236 Skylake
Memory Type	DDR4 ECC UDIMM
Memory Speed	2133 MHz 1866 MHz 1600 MHz
# of DIMM's	4
Max Memory Size	64 GB
Integrated GPU	Aspeed AST2400
# of PCIe x4 3.0	1
# of PCIe x8 3.0	2
# of USB Ports	2 x USB 3.0 (rear) 2 x USB 3.0 (header) 1 x USB 3.0 Type A 2 x USB 2.0 (rear) 4 x USB 2.0 (header)
# of SATA Ports	8
# of SATA DOM power	2
Storage Controllers	8 x AHCI iSATA 6Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports	1 x Fast UART 16550 (rear) 1 x Fast UART 16550 (header)
# of 1GbE Ports	4 x RJ45
Network Controllers	Intel i210 Quad Port Gigabit Ethernet
Integrated BMC	IPMI Dedicated RJ45
BMC chip	Aspeed AST2400
TPM	1 x TPM 1.2 20-pin Header
Uwagi	PCI-Express Slots Configuration: 1x PCI-E 3.0 x8 (in x16) slot 1x PCI-E 3.0 x4 (in x8) slot M.2 Interface: PCI-E 3.0 x2 M.2 Form Factor: 2280

Product SKUs

MBD-X11SSH-LN4F • X11SSH-LN4F (Bulk Pack)

Physical Stats

Form Factor • Micro-ATX

Dimensions • 9.6" x 9.6" (24.38cm x 24.38cm)

Processor/Cache

CPU

- Intel® 6th Generation Core™ i3 series
- Intel® Celeron®
- Intel® Pentium®
- Intel® Xeon® processor E3-1200 v5 series
- Socket H4 (LGA 1151) supported; CPU TDP support 80W

System Memory

Memory Capacity

- 64GB Unbuffered ECC UDIMM, DDR4-2133MHz, in 4 DIMM slots
- 2133/1866/1600MHz ECC DDR4

Memory Type

SDRAM 72-bit, 288-pin (UDIMM) gold-plated DIMMs

DIMM Sizes

- 4GB, 8GB, 16GB

Memory Voltage

- 1.2 V

Error Detection

- Corrects single-bit errors
- Detects double-bit errors (using ECC memory)

On-Board Devices

Chipset

- Intel® C236

SATA

- Intel® C236 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10

Network Controllers

- Quad LAN with Intel® Ethernet Controller I210-AT

Graphics

- Aspeed AST2400 BMC

Input / Output

USB

- 6 USB 2.0 ports (2 rear, 4 via header)
- 5 USB 3.0 ports (2 rear, 2 via header, 1 Type A)

Video Output

- 1 VGA
- 1 Aspeed AST2400 BMC

Serial Port / Header

- 2 COM Ports (1 rear, 1 header)

TPM

- Header

Expansion Slots

PCI-E

- 1 PCI-E 3.0 x8 (in x16 slot)
- 1 PCI-E 3.0 x8
- 1 PCI-E 3.0 x4 (in x8 slot)
- M.2 Interface: PCIe 3.0 x2
- M.2 Form Factor: 2280

System BIOS

BIOS Type

- 128Mb SPI Flash EEPROM with AMI BIOS
- Plug and Play (PnP)
- APM 1.2
- PCI 2.3
- DMI 2.3

BIOS Features

- ACPI 1.0 / 2.0 / 3.0 / 4.0
- USB Keyboard support
- Hardware BIOS Virus protection
- SMBIOS 2.7.1
- UEFI 2.3.1
- RTC (Real Time Clock) Wakeup

Management

Software

- Intel® Node Manager, IPMI2.0, NMI, SPM, SSM, SUM, SuperDoctor® 5, Watchdog

Power Configurations

- ACPI Power Management
- Power-on mode for AC power recovery

PC Health Monitoring

Voltage

- +12V, +3.3V, +5V, +5V standby, Chassis intrusion header, Monitors CPU voltages, Supports system management utility, System level control, VBAT

FAN

- 5x 4-pin fan headers (up to 5 fans), Fan speed control, Overheat LED indication, Thermal control tachometer fan connectors

Temperature

- PECI
- Thermal Monitor 2 (TM2) support
- Monitoring for CPU and chassis environment
- CPU thermal trip support

LED

- CPU / System Overheat LED
- UID/Remote UID

Other Features

- Control of power-on for recovery from AC power loss, CPU thermal trip support for processor protection, M.2 NGFF connector, VHD, WOL

Operating Environment

Operating Temperature Range

- 0°C ~ 50°C (32°F ~ 122°F)

Non-Operating Temperature Range

- -40°C - 70°C (-40°F - 158°F)

Operating Relative Humidity Range

- 8% - 90% (non-condensing)

Non-Operating Relative Humidity Range

Strona firmowa produktu:
<https://www.superstorage.pl/supermicro-mbd-x11ssh-ln4f-single-skt-intel-c236-chipset-sata-4xgbe-ipmi-m2-bulk-p-2583.html>