

Supermicro SuperChassis SC113MTQ-R400CB 1U 8xSFF RED PSU

Kod producenta: CSE-113MTQ-R400CB



Chassis Form Factor	Rack 1U
# of 2.5 hot-swap bays	8
Power Supply	Redundant
PSU Wattage	400W
Chassis Dimensions	437 x 43 x 508mm



Product SKUs

CSE-113MTQ-R400CB • SuperChassis
113MTQ-R400CB (**Black**)

Form Factor

19.98" Depth 1U Rackmount Chassis - support
M-ATX (9.6" x 9.6") and ATX (12" x 10") motherboard

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

- Height • 1.7" (43mm)
- Width • 17.2" (437mm)
- Depth • 19.98" (508mm)
- Packaging • 24" (W) x 8.5" (H) x 30" (L)
- Weight • Net Weight: 21 lbs (9.5kg)
• Gross Weight: 33 lbs (15kg)
- Available Color • Black

Expansion Slots

- 1x Full-height AOC expansion slot

Drive Bays

- Hot-swap • 8x 2.5" Hot-swap SAS2 (6Gb/s) / SATA
HDD trays
SAS or enterprise SATA HDD only
recommended

SAS / SATA Backplane

1x 1U SAS / SATA backplane

Peripheral Drives

- DVD-ROM • Slim DVD-ROM drive or Front USB

Front Panel

- Buttons • Power On/Off button
• System Reset button
• UID button
- LEDs • Power status LED
• HDD activity LED
• 2x Network activity LEDs
• Universal Information (UID) LED

Motherboard (for CSE-113MTQ-R400CB)

- [X10SL7-F](#)
- [X10SLH-F](#)
- [X10SLL+-F](#)
- [X10SLL-F](#)
- [X10SLM+-F](#)
- [X10SLM-F](#)
- [X10SLM-F](#)
- [X9DBL-3F](#)
- [X9DBL-iF](#)
- [X9DBL-i](#)
- [X9SCL](#)
- [X9SCL-F](#)
- [X9SCL+-F](#)
- [X9SCM](#)
- [X9SCM-F](#)
- [X9SCM-iiF](#)
- [X9SRH-7F](#)
- [X9SRH-7TF](#)
- [X9SRi](#)
- [X9SRi-3F](#)
- [X9SRi-F](#)

System Cooling

- Fans • 4x 40x28mm high-efficiency PWM fans
• 2x additional fans optional; 6x fans total maximum

Operating Environment (System)

- Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range
- Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range
- Operating Relative Humidity • 8% ~ 90% (non-condensing)
Range
- Non-Operating Relative Humidity • 5% - 95% (non-condensing)
Range

Power Supply

- 400W Redundant Power Supplies w/Power Distributor, PMBus 1.2, I²C, and PFC
- AC Input • 100-240V, 50-60Hz, 6-3A
- DC Output • +5V standby: 3A
• +12V: 33A
- DC Output • +5V: 25A
With Power • +3.3V: 25A
Distributor • -12V: 0.6A

Regulatory (Power Supply)

- USA - UL listed, FCC
- Canada - CUL listed
- Power Supply Safety / EMC • EN 60950/IEC 60950-Compliant
- Europe/CE Mark

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc113mtq-r400cb-1u-8xsff-red-psu-p-2665.html>