

Supermicro SuperChassis SC113TQ-700CB 1U 8xSFF FIX PSU

Kod producenta: CSE-113TQ-700CB



Chassis Form Factor	Rack 1U
# of 2.5 hot-swap bays	8
Power Supply	Fixed
PSU Wattage	700W
Chassis Dimensions	437 x 43 x 597mm

Product SKUs



CSE-113TQ-700CB • SuperChassis 113TQ-700CB

Form Factor



- 1U Chassis for motherboard support size: (12" x 13")

Processor Support



- Dual, single Intel® / AMD processors

Dimensions



Height	- 1.7" (43 mm)
Width	- 17.2" (437 mm)
Depth	- 23.5" (597 mm)
Gross Weight	- 35 lbs (15.88 kg)
Packaging (W x H x L)	- 25" (635 mm) x 9" (229 mm) x 33" (838 mm)
Available Color	- Black

Expansion Slots



- 1 full-height & full-length expansion slot(s)

Drive Bays



- 8 x 2.5" hot-swap SAS/SATA drive bay
- SAS or enterprise SATA HDD only recommended

Backplane



- 8-port 1U TQ (W/ AMI 9072) backplane, support up to 8x 2.5-inch SAS/SATA HDD/SSD

Peripheral Drives



- 1 x Slim DVD-ROM Drive

Front Panel



- | | |
|---------|------------------------------------|
| Buttons | - Power On/Off button |
| | - System Reset Button |
| | - Unit Identification (UID) button |
| | - 2 Network Activity LEDs |
| LEDs | - HDD activity LED |
| | - Power Status LED |

Systems Cooling



- | | |
|------|---|
| Fans | - 4 x 40x56mm counter-rotation PWM fan(s) |
|------|---|

Operating Environment (System)



- | | |
|---------------------------------------|--------------------------------|
| Operating Temperature Range | - 5°C - 35°C (41°F - 95°F) |
| Non-Operating Temperature Range | - -40°C - 70°C (-40°F - 158°F) |
| Operating Relative Humidity Range | - 8% - 90% (non-condensing) |
| Non-Operating Relative Humidity Range | - 5% - 95% (non-condensing) |

Power Supply

1U 700W hot swap redundant power supply.

- | | |
|------------------------------|--|
| Power Efficiency | - 89% |
| Total Output Power and Input | - 700W with Input 100 - 240Vac |
| AC Input Frequency | - 50-60Hz |
| Dimensions (L x W x H) | - 346 x 76 x 40 mm |
| Output Type | - Backplanes (gold finger) |
| +12V | - Max: 58A / Min: 0.5A (100Vac - 240Vac) |
| +5Vsb | - Max: 4A / Min: 0A |
| | - PDB-PT815-8824 |
| | - O/P: 120/66A |
| Power Distributor | - +5V Max: 24A |
| | - +3.3V Max: 21A |
| | - -12V Max: 0.6A |

Regulatory (Power Supply)



- | | |
|---------------------------|---------------|
| | - BSMI |
| Power Supply Safety / EMC | - CCC |
| | - CE/EMC |
| | - FCC class A |
| | - TUV/CB |
| | - UL/CUL |

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc113tq-700cb-1u-8xsff-fix-psu-p-2877.html>