

Supermicro SuperServer SYS-F619P2-RC1 4U FatTwin^4 DP 8x6SFF LSI 3108 RED PSU

Kod producenta: SYS-F619P2-RC1



Chassis Form Factor	Rack 4U
# of systems (nodes)	8
CPU Socket	LGA 3647 (Socket P)
# of CPU sockets (per node)	2
Supported CPU's	Intel Xeon Scalable 1st Gen Intel Xeon Scalable 2nd Gen
Max CPU TDP	165 W
Chipset	Intel C621
Memory Type	DDR4 ECC LRDIMM DDR4 ECC RDIMM
Memory Speed	2666 MHz 2400 MHz 2133 MHz
# of DIMM's (per node)	12
Max Memory Size (per node)	1536 GB
Integrated GPU	Aspeed AST2500
# of 2.5 hot-swap bays (per node)	6
Backplanes	SAS/SATA
# of PCIe x16 3.0 (per node)	2
# of USB Ports (per node)	2 x USB 3.0 (rear)
# of SAS Ports (per node)	6
Storage Controllers	LSI 3108 12Gb/s HW RAID
Network Controllers	SIOM Networking AOC Matrix
Integrated BMC	IPMI Dedicated RJ45
BMC chip	Aspeed AST2500
Power Supply	Redundant
PSU Wattage	2200 W
PSU Certification	80+ Titanium
Chassis Dimensions	448 x 177 x 737 mm
Uwagi	4xNVMe U.2 option

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

UWAGA !!!

Oferowany produkt to platforma serwerowa służąca do budowy swojej własnej konfiguracji serwera (nie zawiera CPU, RAM czy HDD).
Jeżeli potrzebujesz gotowy serwer super storage, RAM, płyty DVD i inne opcjami skontaktuj się z nami.
Copyright © 2024 www.superstorage.pl, 26 kwietnia 2024

wyślij do nas zapytanie. Posiadamy najlepsze ceny i dostępność na pełne konfiguracje. Zapewniamy pełne wsparcie techniczne do zakupionych u nas serwerów.

Product SKUs		Chassis	
SYS-F619P2-RC1 • SuperServer F619P2-RC1 (Black)		Form Factor	• 4U Rackmount
Motherboard		Model	• CSE-F418BC2-R2K20BP
Super X11DPFR-SN		Dimensions and Weight	
Processor/Cache		Width	• 17.63" (448mm)
CPU	• Dual Socket P (LGA 3647) • Intel® Xeon® Scalable Processors, Dual UPI up to 10.4GT/s • Support CPU TDP 70-165W with IVR	Height	• 6.96" (177mm)
Cores	• Up to 28 Cores with Intel® HT Technology	Depth	• 29" (737mm)
System Memory		Package	• 28.3" (W) x 15.0" (H) x 42.4" (D)
Memory Capacity	• 12 DIMM slots • Up to 1.5TB ECC 3DS LRDIMM, 1.5TB ECC RDIMM, DDR4 up to 2666MHz	Weight	• Net Weight: 150 lbs (68.04 kg) • Gross Weight: 200 lbs (90.71 kg)
Memory Type	• 2666/2400/2133MHz ECC DDR4 SDRAM	Available Colors	• Black
On-Board Devices		Front Panel	
Chipset	• Intel® C621 chipset	Buttons	• Power On/Off button • UID button • Power status LED • Hard drive activity LED
SAS	• SAS3 (12Gbps) via Broadcom 3108 • HW RAID	LEDs	• Network activity LEDs • Information LED (UID, Fan failure, Overheat)
Network Controllers	• Flexible networking via SIOM	Expansion Slots (per node)	
IPMI	• Support for Intelligent Platform Management Interface v.2.0 • IPMI 2.0 with virtual media over LAN and KVM-over-LAN support	PCI-Express	• 1 PCI-E 3.0 x16 (Low-profile) • 1 PCI-E 3.0 x16 (SIOM)
Graphics	• ASPEED AST2500 BMC	Drive Bays (per node)	
Input / Output (per node)		Hot-swap	• 6 Hot-swap 2.5" SAS3/SATA3 or 2 Hot-swap 2.5" SAS3/SATA3 + 4 optional NVMe U.2
SAS	• 6 SAS3 (12Gbps) ports	M.2	• M.2 Support
NVMe	• 4 NVMe U.2 option	Backplane	
LAN	• SIOM flexible Network card	1 SAS/SATA backplane	
USB	• 1 RJ45 Dedicated IPMI LAN port	System Cooling (per node)	
VGA	• 2 USB 3.0 ports (rear) • 1 VGA port	Fans	• 3x 4cm 20k RPM middle fans
System BIOS		Power Supply	
BIOS Type	• 128Mb SPI Flash EEPROM with AMI BIOS	2200W Redundant Power Supplies with PMBus	
Management		Total Output Power and Input	• 1200W with Input 100-127Vac • 1800W with Input 200-220Vac • 1980W with Input 220-230Vac • 2090W with Input 230-240Vac • 2200W with Input 220-240Vac (for UL/cUL use only) • 2090W with Input 230-240Vdc (for CCC only)
Software	• Intel® Node Manager • IPMI 2.0 • KVM with dedicated LAN • SuperDoctor® 5 • Watch Dog	AC Input Frequency	• 50-60Hz
Power Configurations	• ACPI Power Management	Dimension (W x H x L)	• 76 x 40 x 336 mm
PC Health Monitoring		+12V	• Max: 100A / Min: 0A (100-127Vac) • Max: 150A / Min: 0A (200-220Vac) • Max: 165A / Min: 0A (220-230Vac) • Max: 174.17A / Min: 0A (230-240Vac) • Max: 183.3A / Min: 0A (220-240Vac)
CPU	• Monitors for CPU Cores, Chipset Voltages, Memory. • 4+1 Phase-switching voltage regulator	5VSB	• Max: 1A / Min: 0A
FAN	• Fans with tachometer monitoring • Status monitor for speed control • Pulse Width Modulated (PWM) fan connectors	Output Type	• Backplanes (gold finger)
Temperature	• Monitoring for CPU and chassis environment • Thermal Control for fan connectors		
		Certification	UL/cUL/CB/BSMI/CE/CCC Titanium Level [Cert. in progress]
		Operating Environment	
		RoHS	• RoHS Compliant • Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) • Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)
		Environmental Spec.	• Operating Relative Humidity: 8% to 90% (non-condensing) • Non-operating Relative Humidity: 5% to 95% (non-condensing)

Strona firmowa produktu:
<https://www.superstorage.pl/supermicro-superserver-sys-f619p2-rc1-4u-fattwin4-dp-8x6sff-lsi-3108-red-psu-p-3431.html>