

Supermicro SuperChassis SC514-R407W 1U 2xSFF RED PSU

Kod producenta: CSE-514-R407W



Chassis Form Factor	Rack 1U
# of 2.5 fixed bays	2
Power Supply	Redundant
PSU Wattage	400W
PSU Certification	80+ Platinum

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs	☒ Servers (for CSE- 514-R407W)
CSE-514-R407W • SuperChassis 514-R407W	☒ 1019S-WR
Form Factor	
☒ • Support WIO MB	Systems Cooling
Processor Support	☒
☒ • Dual and Single Intel® and AMD processors	Fans - 4 x 40x56mm PWM fan(s) - Optional 2 x fans for AOC cooling
Dimensions	Operating Environment (System)
☒	☒
Height - 1.7" (43 mm)	Operating Temperature Range - 5°C - 35°C (41°F - 95°F)
Width - 17.2" (437 mm)	Non-Operating Temperature Range - -40°C - 70°C (-40°F - 158°F)
Depth - 16.9" (429 mm)	Operating Relative Humidity Range - 8% - 90% (non-condensing)
Gross Weight - 18 lbs (8.16 kg)	Non-Operating Relative Humidity Range - 5% - 95% (non-condensing)
Packaging (W x H x L) - 27" (686 mm) x 8" (203 mm) x 24" (610 mm)	Power Supply
Available Color - No Paint	1U 400W Redundant Power Supply Platinum with PMBUS, W54.5xL220xH40mm
Expansion Slots	Power Efficiency - 94%
☒ - 2 full height expansion slot(s)	Total Output Power and Input - 400W with Input 100 - 240Vac - 400W with Input 200 - 240Vdc
- 1 low-profile expansion slot(s)	AC Input Frequency - 50-60Hz
Drive Bays	Dimensions (L x W x H) - 220 x 54.5 x 40 mm
☒ - Upto 2 x 2.5" fixed with bracket	Output Type - Backplanes (gold finger)
Front Panel	+12V - Max: 33A (100Vac - 240Vac)
☒	+5Vsb - Max: 3A / Min: 0A
Buttons - Power On/Off button	Certification - ☒ Platinum Certified
- System Reset Button	Regulatory (Power Supply)
- 2 Network Activity LEDs	☒
- Fan Fail/System Over Heat LED	- BSMI
- HDD activity LED	Power Supply Safety / EMC
- Power Status LED	- CCC
	- CE/EMC
	- FCC class A
	- UL/CB

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc514-r407w-1u-2xsff-red-psu-p-3496.html>