

Supermicro SuperServer SYS-F628R3-RTBN+ 4U FatTwin^2 DP 4x8LFF RED PSU

Kod producenta: SYS-F628R3-RTBN+

Chassis Form Factor	Rack 4U
# of systems (nodes)	4
CPU Socket	LGA 2011 (Socket R3)
# of CPU sockets (per node)	2
Supported CPU's	Intel Xeon E5-2600v4 Intel Xeon E5-2600v3
Max CPU TDP	145 W
Chipset	Intel C612 Wellsburg
Memory Type	DDR4 ECC 3DS LRDIMM DDR4 ECC LRDIMM DDR4 ECC RDIMM
Memory Speed	2400 MHz 2133 MHz 1866 MHz 1600 MHz
# of DIMM's (per node)	16
Max Memory Size (per node)	2048 GB
Integrated GPU	Aspeed AST2400
# of 3.5 hot-swap bays (per node)	8
Backplanes	SAS2/SATA3
# of PCIe x16 3.0 (per node)	1
# of USB Ports (per node)	2 x USB 3.0 (rear)
# of SATA Ports (per node)	10
Storage Controllers	6 x AHCI iSATA 6Gb/s 4 x sSATA 6Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports (per node)	1 x Fast UART 16550 (header)
# of 1GbE Ports (per node)	2 x RJ45
Network Controllers	Intel i350 Dual Port Gigabit Ethernet
Integrated BMC	IPMI 2.0 KVM-over-LAN Virtual Media over LAN IPMI Dedicated RJ45 PHY
BMC chip	Aspeed AST2400
TPM	1 x TPM 1.2 20-pin Header
Power Supply	Redundant
PSU Wattage	1280W
PSU Certification	80+ Platinum
Chassis Dimensions	448 x 177 x 737mm
Uwagi	HDD bays configuration: Optional NVMe support Note: NVMe support requires 2 CPUs installed PCI-Express Slots Configuration: 1xMicro Low Profile PCI-E 3.0 x8 slot

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs		Chassis	
SYS-F628R3-RTBN+	• SuperServer F628R3-RTBN+ (Black)	Form Factor	• 4U Rackmount
Motherboard		Model	• CSE-F424AS-R1K28B
Super X10DRFR-N		Dimensions and Weight	
Processor/Cache		Width	• 17.63" (448mm)
CPU	• Intel® Xeon® processor E5-2600 v4 [†] / v3 family (up to 145W TDP) * • Dual Socket R3 (LGA 2011)	Height	• 6.96" (177mm)
Cores / Cache	• Up to 22 Cores [†] / Up to 55MB [†] Cache	Depth	• 29" (737mm)
System Bus	• QPI up to 9.6 GT/s	Package	• 28.3" (W) x 15.0" (H) x 42.4" (D)
Note	[†] BIOS version 2.0 or above is required	Weight	• Net Weight: 105 lbs (47.63 kg) • Gross Weight: 150 lbs (68.04 kg)
Note	* Please contact Supermicro Technical Support for additional information about frequency optimized CPUs and specialized system optimization.		
System Memory		Available Colors	• Black
Memory Capacity	• 16x 288-pin DDR4 DIMM slots • Up to 2TB [†] ECC 3DS LRDIMM, 1TB ECC RDIMM	Front Panel	
Memory Type	• 2400 [†] /2133/1866/1600MHz ECC DDR4 SDRAM 72-bit	Buttons	• Power On/Off button • UID button
DIMM Sizes	• RDIMM: 64GB, 32GB, 16GB, 8GB, 4GB • LRDIMM: 64GB, 32GB • 3DS LRDIMM: 128GB	LEDs	• Power status LED • Hard drive activity LED • 2 Network activity LEDs • Information LED (UID, Fan failure, Overheat)
Memory Voltage	• 1.2 V	Expansion Slots (per node)	
Error Detection	• Corrects single-bit errors	PCI-Express	• 1 PCI-E 3.0 x16 (LP) + 1 Micro LP • MicroLP Adapter Matrix (Networking options)
On-Board Devices		Drive Bays (per node)	
Chipset	• Intel® C612 chipset	Hot-swap	• 8x 3.5" Hot-swap HDD trays
SATA	• SATA3 (6Gbps) with RAID 0, 1, 5, 10 • Support for Intelligent Platform Management Interface v.2.0 • IPMI 2.0 with virtual media over LAN and KVM-over-LAN support • ASPEED AST2400 BMC	Backplane	
IPMI	• Intel® i350-AM2 Dual Port Gigabit Ethernet • Virtual Machine Device Queues reduce I/O overhead • Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output • 1x Realtek RTL8201N PHY (dedicated IPMI)	• 1 SAS/SATA backplane • 1 SAS/SATA/NVMe hybrid (2 slots) Note: NVMe support requires 2 CPUs installed	
Network Controllers	• ASPEED AST2400 BMC	System Cooling (per node)	
Graphics	• ASPEED AST2400 BMC	Fans	• 2x 8cm 11k RPM middle fans
Input / Output (per node)		Power Supply	
Serial ATA	• 10 SATA3 (6Gbps) ports	1280W Redundant High-efficiency Digital Power Supplies w/ PMBus 1.2	
LAN	• 2 RJ45 Gigabit Ethernet LAN ports • 1 RJ45 Dedicated IPMI LAN port	AC Input	• 1000W Output @ 100-140V, 8-12A, 50-60Hz • 1280W Output @ 180-240V, 6-8A, 50-60Hz
USB	• 2 USB 3.0 ports	DC Output	• 1000W: +12V/83A; +5Vsb/4A • 1280W: +12V/106.7A, +5Vsb/4A
VGA	• 1 VGA port	Certification	 Platinum Certified [Test Report]
Management			
Software	• SuperDoctor® 5 • Watch Dog • NMI • IPMI 2.0 • SUM and SSM	System BIOS	
Power Configurations	• ACPI / APM Power Management • Power-on mode for AC power recovery	BIOS Type	• 128Mb SPI Flash EEPROM with AMI BIOS • Plug and Play (PnP) • APM 1.2 • PCI 2.2 • ACPI 1.0 / 2.0 • USB Keyboard support • SMBIOS 2.3 • UEFI
		Operating Environment / Compliance	
		RoHS	• RoHS Compliant
		Environmental Spec.	• Operating Temperature: 10°C to 35°C (50°F to 95°F) • Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) • Operating Relative Humidity: 8% to 90% (non-condensing) • Non-operating Relative Humidity: 5% to 95% (non-condensing)

UWAGA !!!

Oferowany produkt to platforma serwerowa służąca do budowy swojej własnej konfiguracji serwera (

Copyright ©2024 www.superstorage.pl | poniedziałek, 20 maj 2024 Strona: 2 / 3

nie zawiera CPU, RAM czy HDD).

Jeżeli potrzebujesz kupić gotowy serwer wraz z CPU, RAM, HDD/SDD oraz innymi opcjami koniecznie wyślij do nas zapytanie. Posiadamy najlepsze ceny i dostępność na pełne konfiguracje. Zapewniamy pełne wsparcie techniczne do zakupionych u nas serwerów.

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superserver-sys-f628r3-rtbn-4u-fattwin2-dp-4x8lff-red-psu-p-1013.html>