

Supermicro SuperServer SYS-2027TR-HTRF+ 2U Twin^2 DP 4x6SFF RED PSU

Kod producenta: SYS-2027TR-HTRF+

	Chassis Form Factor	Rack 2U
	# of systems (nodes)	4
	CPU Socket	LGA 2011 (Socket R)
	# of CPU sockets (per node)	2
	Supported CPU's	Intel Xeon E5-2600v2 Intel Xeon E5-2600
	Max CPU TDP	135 W
	Chipset	Intel C602 Patsburg
	Memory Type	DDR3 ECC LRDIMM DDR3 ECC RDIMM
	Memory Speed	1866 MHz 1600 MHz 1333 MHz 1066 MHz 800 MHz
	# of DIMM's (per node)	16
	Max Memory Size (per node)	1024 GB
	Integrated GPU	Matrox G200eW
	# of 2.5 hot-swap bays (per node)	6
	Backplanes	SAS3/SATA3
	# of PCIe x8 3.0 (per node)	1
	# of USB Ports (per node)	2 x USB 2.0 (rear) 2 x USB 2.0 (header) 1 x USB 2.0 Type A
	# of SATA Ports (per node)	6
	Storage Controllers	2 x AHCI iSATA 6Gb/s 4 x AHCI iSATA 3Gb/s
	Integrated RAID	0,1,5,10
	# of Serial Ports (per node)	1 x Fast UART 16550 (header)
	# of 1GbE Ports (per node)	2 x RJ45
	Network Controllers	Intel i350 Dual Port Gigabit Ethernet
	Integrated BMC	IPMI 2.0 KVM-over-LAN Virtual Media over LAN IPMI Dedicated RJ45 PHY
	BMC chip	Nuvoton WPCM450
	TPM	1 x TPM 1.2 20-pin Header
	Power Supply	Redundant
	PSU Wattage	1620W
	PSU Certification	80+ Platinum
	Chassis Dimensions	438 x 88 x 679mm
	Uwagi	PCI-Express Slots Configuration: 1xMicro Low Profile PCI-E

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superserver-sys-2027tr-htrf-2u-twin2-dp-4x6sff-red-psu-p-1124.html>