

Supermicro MBD-X10SLH-F, Single SKT, Intel C226 Chipset, SATA, 2xGbE, IPMI

Part number: MBD-X10SLH-F-O



Form Factor	uATX
Dimensions	9.6" x 9.6"
CPU Socket	LGA 1150 (Socket H3)
# of CPU sockets	1
Supported CPU's	Intel Xeon E3-1200v3 Intel Xeon E3-1200v4
Chipset	Intel C226 Lynx Point
Memory Type	DDR3 ECC UDIMM
Memory Speed	1600 MHz 1333 MHz
# of DIMM's	4
Max Memory Size	32 GB
Integrated GPU	Aspeed AST2400
# of PCIe x8 3.0	2
# of PCIe x4 2.0	1
# of USB Ports	2 x USB 3.0 (rear) 1 x USB 3.0 (header) 1 x USB 3.0 Type A 2 x USB 2.0 (rear) 4 x USB 2.0 (header)
# of SATA Ports	6
# of SATA DOM power	1
Storage Controllers	6 x AHCI iSATA 6Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports	1 x Fast UART 16550 (rear) 1 x Fast UART 16550 (header)
# of 1GbE Ports	2 x RJ45
Network Controllers	Intel i210 Dual Port Gigabit Ethernet
Integrated BMC	IPMI 2.0 KVM-over-LAN Virtual Media over LAN IPMI Dedicated RJ45 PHY
BMC chip	Aspeed AST2400
TPM	1 x TPM 1.2 20-pin Header

Product SKUs			
<input type="checkbox"/>		<input type="checkbox"/>	Chassis (Optimized for X10SLH-F)
MBD-X10SLH-F • X10SLH-F (Bulk Pack)		<input type="checkbox"/>	
Physical Stats			<ul style="list-style-type: none"> • SC813MTO-R400CB • SC813MTO-350CB • SC813MTO-441CB • SC113MTO-R400CB • SC113MTO-330CB • SC811TO-441B • SC512F-350B • SC512F-441B • SC825MTO-R700LPB
Form Factor • microATX	1U Chassis:		
Dimensions • 9.6" x 9.6", (24.4cm x 24.4 cm)			
Processor/Cache			
<input type="checkbox"/>			
CPU	2U Chassis:		<ul style="list-style-type: none"> • SC823TO-653LPB • SC213LT-563LPB • SC213LT-600LPB
<ul style="list-style-type: none"> • Intel® Xeon® processor E3-1200 v3/v4 (supports VHD via E3-1285 or E3-1285L) and 4th Gen Core i3, Pentium, Celeron processors • Single Socket H3 (LGA 1150) 	3U Chassis:		<ul style="list-style-type: none"> • SC833T-653B • SC731i-300B • SC732i-865B • SC732i-500B • SC732D2-903B • SC732D2-865B • SC732D2-500B • SC732D4-903B • SC732D4-865B • SC731D-300B • SC732D4-500B • SC733TO-665B • SC733TO-500B • SC745TO-920B • SC745TO-R920B • SC743TO-865B-SQ • SC842i-500B • SC842TO-665B • SC842TO-865B
System Memory			
<input type="checkbox"/>			
Memory Capacity	4x 240-pin DDR3 DIMM sockets	Mid/Mini Tower Chassis:	
	• Supports up to 32 GB DDR3 ECC Un-Buffered memory (UDIMM)		
Memory Type	• 1600MHz ECC DDR3 SDRAM 72-bit, 240-pin gold-plated DIMMs		
DIMM Sizes	• 8GB, 4GB, 2GB, 1GB		
Memory Voltage	• 1.5 V, 1.35 V		
Error Detection	• Corrects single-bit errors	4U / Tower Chassis:	
	• Detects double-bit errors (using ECC memory)		
On-Board Devices			
<input type="checkbox"/>			
Chipset	• Intel® C226 Express PCH	Important Chassis Notes	Intel® Xeon® processor-based motherboards, Revision M chassis is recommended. Please talk to your sales representative for details.
SATA	• SATA3 (6Gbps) w/ RAID 0, 1, 5, 10		
	• Support for Intelligent Platform Management Interface v.2.0		
IPMI	• IPMI 2.0 with virtual media over LAN and KVM-over-LAN support		
	• Intel® i210AT Controllers		
Network Controllers	• Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output	Expansion Slots	
	• 1x Realtek RTL8211E PHY (dedicated IPMI)	<input type="checkbox"/>	
VGA	• BMC integrated Aspeed AST2400	PCI-Express	<ul style="list-style-type: none"> • 1x PCI-E 3.0 x8 (in x16) slot • 1x PCI-E 3.0 x8 slot • 1x PCI-E 2.0 x4 (in x8) slot
Input / Output		System BIOS	
<input type="checkbox"/>		<input type="checkbox"/>	
Serial ATA	• 6x SATA3 (6Gbps) ports	BIOS Type	• 128Mb SPI Flash EEPROM with AMI BIOS
LAN	• 2x Gigabit Ethernet LAN ports	BIOS Features	• DMI (SMBIOS) 2.7
	• 1x RJ45 Dedicated IPMI LAN port		• ACPI 5.0
	• 4x USB 3.0 ports (2 rear, 1 Type-A, 1 via header)		• USB Keyboard support
USB	• 6x USB 2.0 ports (2 rear, 4 via header)	Management	
VGA	• 1x VGA D-Sub Connector	<input type="checkbox"/>	
Serial Port / Header	• 2x COM ports (1 rear, 1 header)	Software	<ul style="list-style-type: none"> • IPMI (Intelligent Platform Management Interface) v2.0 with KVM support • SuperDoctor® III • Watch Dog • NMI • ACPI / ACPM Power Management • Main Switch Override Mechanism • Power-on mode for AC power recovery • Internal/External modem ring-on
DOM	• SATA DOM (Disk on Module) power connector support	Power Configurations	
TPM	• 1x TPM Header		
		PC Health Monitoring	
		<input type="checkbox"/>	
		Voltage	<ul style="list-style-type: none"> • Monitors for CPU Cores, +12V, +3.3V, +5V, +5V Standby, VBAT, HT, Memory, Chipset Voltages. • 5-Phase-switching voltage regulator with auto-sense from 0.8375V-1.60V • Total of five 4-pin fan headers supporting up to 5 fans • 5x fans with tachometer status monitoring
		FAN	<ul style="list-style-type: none"> • Status monitor for speed control • Status monitor for on/off control • Support 3-pin fans (w/o speed control) • Low noise fan speed control • Pulse Width Modulated (PWM) fan connectors • Monitoring for CPU and chassis environment
		Temperature	<ul style="list-style-type: none"> • CPU thermal trip support • FC temperature sensing logic • Thermal Monitor 2 (TM2) support • PECI
		LED	<ul style="list-style-type: none"> • CPU / System Overheat LED • +5V Standby alert LED
		Other Features	<ul style="list-style-type: none"> • Chassis intrusion detection • Chassis intrusion header
		<input type="checkbox"/>	
		Operating Environment	
		<input type="checkbox"/>	
		Operating Temperature Range	• 0°C ~ 50°C (32°F ~ 122°F)
		Non-Operating Temperature Range	• -40°C ~ 70°C (-40°F ~ 158°F)
		Operating Relative Humidity Range	• 8% ~ 90% (non-condensing)
		Non-Operating Relative Humidity Range	

Visit us for more info:

<https://www.superstorage.pl/supermicro-mbd-x10slh-single-skt-intel-c226-chipset-sata-2xgbe-ipmi-p-1365.html>