

Supermicro MBD-X10SRA, Single SKT, Intel C612 Chipset, SATA, 2xGbE

Kod producenta: MBD-X10SRA-O



Category	Workstation
Form Factor	ATX
Dimensions	12" x 9.6"
CPU Socket	LGA 2011 (Socket R3)
# of CPU sockets	1
Supported CPU's	Intel Xeon E5-2600v4 Intel Xeon E5-2600v3 Intel Xeon E5-1600v3
Chipset	Intel C612 Wellsburg
Memory Type	DDR4 ECC 3DS LRDIMM DDR4 ECC LRDIMM DDR4 ECC RDIMM DDR4 ECC UDIMM DDR4 non-ECC UDIMM
Memory Speed	2400 MHz 2133 MHz 1866 MHz 1600 MHz
# of DIMM's	8
Max Memory Size	512 GB
# of PCIe x16 3.0	4
# of PCIe x4 2.0	2
# of USB Ports	6 x USB 3.0 (rear) 2 x USB 3.0 (header)
# of SATA Ports	10
Storage Controllers	6 x AHCI iSATA 6Gb/s 4 x sSATA 6Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports	1 x Fast UART 16550 (header)
# of 1GbE Ports	2 x RJ45
Network Controllers	Intel i210-AT Dual Port Gigabit Ethernet
TPM	1 x TPM 1.2 20-pin Header
Uwagi	PCI-Express Slots Configuration: 4x PCI-E 3.0 x16 slots (runs at 16/16/NA/8 or 16/8/8/8) 2x PCI-E 2.0 x1 (in x4) slots

Product SKUs		Chassis (Optimized for X10SRA-F)		
MBD-X10SRA-F -B	• X10SRA-F (Bulk Pack)	Mid/Mini Tower	- SC732D3-903B	
		Chassis:		
Physical Stats	Form Factor • ATX	4U / Tower	- SC743TO-1200B-SQ	
		Chassis:	- SC745BTO-R1K28B-SQ	
Dimensions	• 12" x 9.6", (30.5cm x 24.4cm)	- To support the new generation Intel® Xeon® processor-based motherboards, Revision K chassis is recommended. Please talk to your sales representative for details.		
		Important Chassis Notes		
Processor		Expansion Slots		
CPU	- Intel® Xeon® processor E5-2600 v4 ¹ / v3, E5-1600 v4 ¹ / v3 family or Intel® Core™ i7 series (up to 160W TDP **) - Single Socket R3 (LGA 2011)	PCI-Express	PCI-E slot #1 supports (x4) and slot #4 (x16) is disabled when Intel Core i7-5820K is installed	
Core / Cache	- Up to 22 Cores ¹ / Up to 55MB ¹ Cache			
Note	¹ BIOS version 2.0 or above is required			
Note	** Motherboard supports this maximum TDP. Please verify your system can thermally support			
System Memory		System BIOS		
Memory Capacity	- 8x 288-pin DDR4 DIMM slots - Up to 1TB ECC 3DS LRDIMM - Up to 512GB ECC LRDIMM - Up to 256GB ECC RDIMM - Up to 128GB DDR4 ECC/non-ECC UDIMM (available with Core i7 only)	BIOS Type	- 128Mb SPI Flash EEPROM with AMI BIOS - Plug and Play (PnP) - APM 1.2 - DMI 2.3 - PCI 2.3	
Memory Type	DDR4 SDRAM 72-bit, 288-pin (RDIMM / LRDIMM) / 284-pin gold-plated DIMMs	BIOS Features	- ACPI 1.0 / 2.0 / 3.0 / 4.0 - USB Keyboard support - Hardware BIOS Virus protection - SMBIOS 2.7.1 - UEFI 2.3.1 - RTC (Real Time Clock) Wakeup	
DIMM Sizes	- LRDIMM: 64GB, 32GB - RDIMM: 32GB, 16GB, 8GB, 4GB			
Memory Voltage	- 1.2 V			
Error Detection	- Corrects single-bit errors - Detects double-bit errors (using ECC memory)			
On-Board Devices		Management		
Chipset	- Intel C612 chipset - SATA3 (6Gbps) via C612 controller	Software	- IPMI 2.0 with KVM support - SuperDoctor® 5 - SuperDoctor® III - Watch Dog - ACPI Power Management	
SATA	- RAID 0, 1, 5, 10 support - Intel® i210-AT Dual Port Gigabit Ethernet	Power Configurations	- Keyboard Wakeup from Soft-Off - CPU Fan auto-off in sleep mode - Power-on mode for AC power recovery	
Network Controllers	- Share with IPMI - Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output			
Audio	- RealTek ALC1150 High Definition Audio			
Input / Output		PC Health Monitoring		
SATA	- 10x SATA3 (6Gbps) ports - 2x RJ45 Gigabit Ethernet LAN ports	Voltage	- +12V, +3.3V, +5V, 1.05 (PCH), 1.2V (VDIMM), 3.3V standby, Chassis intrusion header, Monitors CPU voltages, VBAT - Total of 5 fan headers supporting up to 5 fans - 5 fans with tachometer status monitoring	
LAN	- Shared with IPMI - 8x USB 3.0 ports (6 rear + 2 via header)	FAN	- Status monitor for speed control - Status monitor for on/off control - Low noise fan speed control - Pulse Width Modulated (PWM) fan connectors	
USB	- 4 of 8 USB 3.0 ports upgradable to 4x USB 3.1 (10Gbps) (2 rear + 2 via header) (This upgrade is BOM option for OEM only)			
Audio	- 7.1 HD Jacks	Temperature	- Monitoring for CPU and chassis environment - CPU thermal trip support - I°C temperature sensing logic - Thermal Monitor 2 (TM2) support - PECI	
Keyboard/Mouse	- 1 PS/2 Keyboard/Mouse port			
Serial Port / Header	- 1x header	LED	- CPU / System Overheat LED - Suspend static indicator LED	
TPM	- 1x TPM Header			
OS Compatibility		Other Features	- Chassis intrusion detection - Chassis intrusion header - Chipkill support - RoHS	
• Please reference the OS Compatibility Chart for details				

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-mbd-x10sra-single-skt-intel-c612-chipset-sata-2xgbe-p-1388.html>