

Supermicro MBD-X10SRA-F, Single SKT, Intel C612 Chipset, SATA, 2xGbE, IPMI

Kod producenta: MBD-X10SRA-F-O



Form Factor	ATX
Dimensions	12" x 9.6"
CPU Socket	LGA 2011 (Socket R3)
# of CPU sockets	1
Supported CPU's	Intel Xeon E5-2600v3 Intel Xeon E5-1600v3
Chipset	Intel C612 Wellsburg
Memory Type	DDR3 ECC LRDIMM DDR3 ECC RDIMM DDR3 ECC UDIMM DDR3 non-ECC UDIMM
Memory Speed	2133 MHz 1866 MHz 1600 MHz 1333 MHz
# of DIMM's	8
Max Memory Size	512 GB
Integrated GPU	Aspeed AST2400
# of PCIe x16 3.0	4
# of PCIe x4 2.0	2
# of USB Ports	6 x USB 3.0 (rear) 2 x USB 3.0 (header)
# of SATA Ports	10
Storage Controllers	6 x AHCI iSATA 6Gb/s 4 x sSATA 6Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports	1 x Fast UART 16550 (header)
# of 1GbE Ports	2 x RJ45
Network Controllers	Intel i210-AT Dual Port Gigabit Ethernet
Integrated BMC	IPMI 2.0 KVM-over-LAN
BMC chip	Aspeed AST2400
TPM	1 x TPM 1.2 20-pin Header
Uwagi	PCI-Express Slots Configuration: 4x PCI-E 3.0 x16 slots (runs at 16/16/NA/8 or 16/8/8/8) 2x PCI-E 2.0 x1 (in x4) slots

Product SKUs		Chassis (Optimized for X10SRA-F)	
MBD-X10SRA-F -B		Mid/Mini Tower	- SC732D3-903B
Physical Stats		Chassis:	
Form Factor		4U / Tower	- SC743TO-1200B-SQ
Dimensions		Chassis:	- SC745BTQ-R1K28B-SQ
Processor		Important Chassis Notes	- To support the new generation Intel® Xeon® processor-based motherboards, Revision K chassis is recommended. Please talk to your sales representative for details.
CPU	- Intel® Xeon® processor E5-2600 v4 ¹ / v3, E5-1600 v4 ¹ / v3 family or Intel® Core™ i7 series (up to 160W TDP **)		
	- Single Socket R3 (LGA 2011)		
Core / Cache	- Up to 22 Cores ¹ / Up to 55MB ¹ Cache		
Note	¹ BIOS version 2.0 or above is required		
Note	** Motherboard supports this maximum TDP. Please verify your system can thermally support		
System Memory		Expansion Slots	
Memory Capacity	- 8x 288-pin DDR4 DIMM slots	- 4x PCI-E 3.0 x16 slots (runs at 16/16/NA/8 or 16/8/8/8)	
	- Up to 1TB ECC 3DS LRDIMM	- 2x PCI-E 2.0 x1 (in x4) slots	
Memory Type	- Up to 512GB ECC LRDIMM	PCI-Express	PCI-E slot #1 supports (x4) and slot #4 (x16) is disabled when Intel Core i7-5820K is installed
	- Up to 256GB ECC RDIMM		
Memory Type	- Up to 128GB DDR4 ECC/non-ECC UDIMM (available with Core i7 only)	System BIOS	BIOS Type
	- 2400 ¹ / 2133/1866/1600MHz ECC DDR4 SDRAM 72-bit, 288-pin (RDIMM / LRDIMM) / 284-pin gold-plated DIMMs		- 128Mb SPI Flash EEPROM with AMI BIOS
DIMM Sizes	- LRDIMM: 64GB, 32GB	BIOS Features	- Plug and Play (PnP)
	- RDIMM: 32GB, 16GB, 8GB, 4GB		- APM 1.2
Memory Voltage	- 1.2 V	Management	- DMI 2.3
Error Detection	- Corrects single-bit errors		- PCI 2.3
	- Detects double-bit errors (using ECC memory)	Software	- ACPI 1.0 / 2.0 / 3.0 / 4.0
On-Board Devices			- USB Keyboard support
Chipset	- Intel C612 chipset	Power Configurations	- Hardware BIOS Virus protection
SATA	- SATA3 (6Gbps) via C612 controller		- SMBIOS 2.7.1
Network Controllers	- RAID 0, 1, 5, 10 support	PC Health Monitoring	- UEFI 2.3.1
	- Intel® i210-AT Dual Port Gigabit Ethernet		- RTC (Real Time Clock) Wakeup
Audio	- Share with IPMI	Voltage	- +12V, +3.3V, +5V, 1.05 (PCH), 1.2V (VDIMM), 3.3V standby, Chassis intrusion header, Monitors CPU voltages, VBAT
	- Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output		- Total of 5 fan headers supporting up to 5 fans
Audio	- RealTek ALC1150 High Definition Audio	FAN	- 5 fans with tachometer status monitoring
Input / Output			- Status monitor for speed control
SATA	- 10x SATA3 (6Gbps) ports	Temperature	- Status monitor for on/off control
LAN	- 2x RJ45 Gigabit Ethernet LAN ports		- Low noise fan speed control
	- Shared with IPMI	LED	- Pulse Width Modulated (PWM) fan connectors
USB	- 8x USB 3.0 ports (6 rear + 2 via header)		- Monitoring for CPU and chassis environment
Audio	- 4 of 8 USB 3.0 ports upgradable to 4x USB 3.1 (10Gbps) (2 rear + 2 via header) (This upgrade is BOM option for OEM only)	Other Features	- CPU thermal trip support
	- 7.1 HD Jacks		- I°C temperature sensing logic
Keyboard/Mouse	- 1 PS/2 Keyboard/Mouse port	Features	- Thermal Monitor 2 (TM2) support
Serial Port / Header	- 1x header		- PECI
TPM	- 1x TPM Header		- CPU / System Overheat LED
OS Compatibility			- Suspend static indicator LED
• Please reference the OS Compatibility Chart for details			- Chassis intrusion detection
			- Chassis intrusion header
			- Chipkill support
			- RoHS

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-mbd-x10sra-single-skt-intel-c612-chipset-sata-2xgbe-ipmi-p-1389.html>