

# Supermicro SuperServer SYS-5019S-M2 1U UP 4xLFF 2xGbE FIX PSU

Kod producenta: SYS-5019S-M2



|                        |                                                                                                                |
|------------------------|----------------------------------------------------------------------------------------------------------------|
| Chassis Form Factor    | Rack 1U                                                                                                        |
| CPU Socket             | LGA 1151 (Socket H4)                                                                                           |
| # of CPU sockets       | 1                                                                                                              |
| Supported CPU's        | Intel Xeon E3-1200v5<br>Intel Gen. Core i7/i5/i3                                                               |
| Max CPU TDP            | 95 W                                                                                                           |
| Chipset                | Intel C236 Skylake                                                                                             |
| Memory Type            | DDR4 ECC/Non-ECC UDIMM                                                                                         |
| Memory Speed           | 2133 MHz<br>1866 MHz<br>1600 MHz                                                                               |
| # of DIMM's            | 4                                                                                                              |
| Max Memory Size        | 64 GB                                                                                                          |
| Integrated GPU         | Aspeed AST2400                                                                                                 |
| # of 3.5 hot-swap bays | 4                                                                                                              |
| Backplanes             | SAS/SATA                                                                                                       |
| # of PCIe x16 3.0      | 1                                                                                                              |
| # of USB Ports         | 2 x USB 3.0 (rear)<br>2 x USB 3.0 (header)<br>2 x USB 2.0 (rear)<br>6 x USB 2.0 (header)<br>1 x USB 2.0 Type A |
| # of SATA Ports        | 4                                                                                                              |
| # of Super DOM         | 1                                                                                                              |
| Storage Controllers    | 4 x AHCI iSATA 6Gb/s                                                                                           |
| Integrated RAID        | 0,1,5,10                                                                                                       |
| # of Serial Ports      | 2 x Fast UART 16550 (header)                                                                                   |
| # of 1GbE Ports        | 2 x RJ45                                                                                                       |
| Network Controllers    | Intel i210 Single Port Gigabit Ethernet<br>Intel i219LM Single Port Gigabit Ethernet                           |
| Integrated BMC         | IPMI 2.0<br>KVM-over-LAN<br>Virtual Media over LAN<br>IPMI Dedicated RJ45 PHY                                  |
| BMC chip               | Aspeed AST2400                                                                                                 |
| TPM                    | 1 x TPM 1.2 20-pin Header                                                                                      |
| Power Supply           | Fixed                                                                                                          |
| PSU Wattage            | 350W                                                                                                           |
| PSU Certification      | 80+ Platinum                                                                                                   |
| Chassis Dimensions     | 437 x 43 x 594mm                                                                                               |
| Uwagi                  | PCI-Express Slots Configuration:<br>1x PCI-E 3.0 x16 FH, FL Slot                                               |

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superserver-sys-5019s-m2-1u-up-4xlff-2xgbe-fix-psu-p-1897.html>