

# Supermicro SuperServe SYS-5029S-TN2 Mini-Tower UP 4xLFF 2xSFF FIX PSU

**Part number: SYS-5029S-TN2**



*Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:*

Product SKUs	<input type="checkbox"/>	Chassis	<input type="checkbox"/>
<input type="checkbox"/> SYS-5029S-TN2 • SuperServer 5029S-TN2 (Black)		Form Factor	• Mini Tower
Motherboard	<input type="checkbox"/>	Model	• <a href="#">CSE-721TQ-250B</a>
<input type="checkbox"/> <a href="#">Super X11SSV-Q</a>		Dimensions and Weight	<input type="checkbox"/>
Processor/Cache		Height	• 9.45" (240mm)
CPU	<ul style="list-style-type: none"> <li>• Intel® 6th Gen Core i7/i5/i3 series, Intel® Celeron®, Intel® Pentium® processors; CPU TDP support up to 80W TDP</li> <li>• Single Socket H4 (LGA 1151)</li> </ul>	Width	• 8.27" (210mm)
System Memory	<input type="checkbox"/>	Depth	• 1.1" (279mm)
Memory Capacity	<ul style="list-style-type: none"> <li>• 2x 260-pin DDR4 SODIMM slots</li> <li>• Up to 32GB DDR4 Non-ECC UDIMM</li> <li>• 2133/1866/1600MHz Non-ECC</li> </ul>	Weight	• Gross Weight: 15 lbs (6.8 kg)
Memory Type	DDR4 SDRAM 72-bit, 260-pin gold-plated SODIMMs	Available Colors	• Black
DIMM Sizes	• 16GB, 8GB, 4GB	Front Panel	<input type="checkbox"/>
Memory Voltage	• 1.2 V	Buttons	<ul style="list-style-type: none"> <li>• Power On/Off button</li> <li>• System Reset button</li> <li>• Power LED</li> <li>• Hard drive activity LED</li> <li>• Network activity LEDs</li> <li>• System Overheat LED</li> </ul>
On-Board Devices	<input type="checkbox"/>	LEDs	
Chipset	<ul style="list-style-type: none"> <li>• Intel® Q170 Express Chipset</li> <li>• Onboard controller for 4x SATA3 (6Gbps) ports with RAID 0, 1, 5, 10</li> <li>• Intel® PHY i219LM + Intel® i210AT Gigabit Ethernet LAN Controllers</li> </ul>	Expansion Slots	<input type="checkbox"/>
SATA		PCI-E	<ul style="list-style-type: none"> <li>• 1x PCI-E 3.0 x16 slot</li> <li>• 1x Mini-PCIe with mSATA support</li> </ul>
Network Controllers	<ul style="list-style-type: none"> <li>• Virtual Machine Device Queues reduce I/O overhead</li> <li>• Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output</li> </ul>	Drive Bays	<input type="checkbox"/>
Audio	• RealTek ALC 888S High Definition Audio	HDD	<ul style="list-style-type: none"> <li>• 4x 3.5" Hot-swap drive bays</li> <li>• 2x 2.5" internal drive bays</li> </ul>
Input / Output	<input type="checkbox"/>	Peripheral	• 1x slim DVD-ROM drive bay (shared with 1x 2.5" internal drive bay)
Serial ATA	<ul style="list-style-type: none"> <li>• 5x SATA 3.0 ports (6Gbps) including 1x mSATA</li> <li>• Raid 0, 1, 5, 10</li> </ul>	Power Supply	<input type="checkbox"/>
LAN	• 2x RJ45 Gigabit Ethernet LAN ports	250W Flex ATX Multi-output Bronze Power Supply	
USB	<ul style="list-style-type: none"> <li>• 4x USB 3.0 ports (rear)</li> <li>• 2x USB 2.0 ports (front)</li> <li>• 1x USB 2.0 Type A</li> </ul>	AC Voltage	• 100 - 240V, 50 - 60Hz, 5Amp
Audio	• 2 port jack	+5V	• Max:14 Amp; Min:0.5 Amp
Video/Display	• 1x HDMI, 1x DP (Display Port), 1x DVI-I, Intel® HD Graphics, 3x Independent Displays	+12V	• Max:18 Amp; Min:1 Amp @100V-240V
Serial Port / Header	• 2x COM ports (2 rear)	-12V	• Max: 3 Amp; Min: 0 Amp
DOM	• SATA DOM (Disk on Module) power connector support	+3.3V	• Max: 12 Amp Min: 0.3Amp
TPM	• 1x TPM 20-pin Header	5VSB	• Max: 2.5 Amp Min: 0 Amp
Management	<input type="checkbox"/>	Certification	<input type="checkbox"/> <a href="#">Bronze Certified</a>
Software	<ul style="list-style-type: none"> <li>• <a href="#">SuperDoctor® 5</a></li> <li>• Watch Dog</li> <li>• AMT</li> <li>• NMI</li> <li>• vPro</li> </ul>	System BIOS	<input type="checkbox"/>
		BIOS Type	<ul style="list-style-type: none"> <li>• 128Mb SPI Flash EEPROM with AMI UEFI BIOS</li> <li>• Plug and Play (PnP)</li> <li>• DMI 2.3</li> <li>• PCI 3.0</li> <li>• ACPI 5.0</li> </ul>
		BIOS Features	<ul style="list-style-type: none"> <li>• USB Keyboard support</li> <li>• Hardware BIOS Virus protection</li> <li>• SMBIOS 3.0</li> <li>• UEFI 2.3.1</li> <li>• RTC (Real Time Clock) Wakeup</li> </ul>
		Operating Environment / Compliance	<input type="checkbox"/>
		RoHS	<ul style="list-style-type: none"> <li>• RoHS Compliant</li> <li>• Operating Temperature: 0°C to 40°C (32°F to 104°F)</li> <li>• Non-operating Temperature: -40°C to 70°C (-40°F to 158°F)</li> </ul>
		Environmental Spec.	<ul style="list-style-type: none"> <li>• Operating Relative Humidity: 8% to 90% (non-condensing)</li> <li>• Non-operating Relative Humidity: 5% to 95% (non-condensing)</li> </ul>

## UWAGA !!!

*Oferowany produkt to platforma serwerowa służąca do budowy swojej własnej konfiguracji serwera (nie zawiera CPU, RAM czy HDD ).*

*Jeżeli potrzebujesz kupić gotowy serwer wraz z CPU, RAM, HDD/SDD oraz innymi opcjami koniecznie wyślij do nas zapytanie. Posiadamy najlepsze ceny i dostępność na pełne konfiguracje. Zapewniamy pełne wsparcie techniczne do zakupionych u nas serwerów.*

Visit us for more info:

<https://www.superstorage.pl/supermicro-superserve-sys-5029s-tn2-mini-tower-up-4xlf-2xsff-fix-psu-p-2047.html>