

Supermicro SuperChassis SC216BE1C-R920LPB 2U 24xSFF RED PSU

Kod producenta: CSE-216BE1C-R920LPB



Chassis Form Factor	Rack 2U
# of 2.5 hot-swap bays	24
Power Supply	Redundant
PSU Wattage	920W
PSU Certification	80+ Platinum
Uwagi	Single Expander SAS3 Backplane

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-216BE1C-R920LPB • SuperChassis 216BE1C-R920LPB (Black)

Form Factor

2U chassis support for max. motherboard size - 13" x 13.68", E-ATX and ATX

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Width • 17.2" (437mm)
Height • 3.5" (89mm)
Depth • 24.8" (630mm)
Packaging • 26.5" (W) x 10.5" (H) x 38" (L)
Gross Weight 53 lbs (24kg)
Available Color Black

Expansion Slots

• 7x low-profile expansion slots

Drive Bays

Hot-swap 24x 2.5" SAS / SATA Hot-swap drive trays
SAS or enterprise SATA HDD only recommended

Backplane

SAS3 12Gb/s Single Expander Backplane

Front Panel

Buttons • Power On/Off button
• System Reset button
• Power LED
• Hard drive activity LED
LEDs • 2x Network activity LEDs
• System Overheat LED
• Power fail LED

Motherboard (for CSE-216BE1C-R920LPB)

X10DRC-LN4+	X10DRC-T4+
X10DRH-C	X10DRH-CLN4
X10DRH-CT	X10DRH-I
X10DRH-iT	X10DRi
X10DRi-LN4+	X10DRi-T
X10DRi-T4+	X10SRH-CLN4F
X9DAi	

System Cooling

Fans 3x 80mm 7000 RPM PWM fans
Optional 5x 60mm middle fan kit:
MCP-320-82603-0N

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range
Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range
Operating Relative Humidity • 8% ~ 90% (non-condensing)
Range
Non-Operating Relative Humidity • 5% - 95% (non-condensing)
Range

Power Supply
920W Redundant High-Efficiency Power Supplies w/ Power Distributor, PMBus 1.2, PFC, and PFC
AC Input • 100-240 V, 50-60 Hz, 11-4.5 Amp
DC Output • +5V standby: 4A
• +12V: 75A
• +5V: 45A
With Power Distributor • +3.3V: 24A
• -12V: 0.6A

Certification  **Platinum Certified**
[\[Test Report \]](#)

Regulatory (Power Supply)

Power Supply Safety / EMC • USA - UL listed
• Canada - CUL listed
• Germany - TUV Certified
• EN 60950/IEC 60950-Compliant
• CB Report
• CCC Certification

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc216be1c-r920lpb-2u-24xsff-red-psu-p-2174.html>