

# Supermicro SuperChassis SC813MTQ-350CB 1U 4xLFF FIX PSU

Kod producenta: CSE-813MTQ-350CB



|                        |                  |
|------------------------|------------------|
| Chassis Form Factor    | Rack 1U          |
| # of 3.5 hot-swap bays | 4                |
| Power Supply           | Fixed            |
| PSU Wattage            | 350W             |
| PSU Certification      | 80+ Gold         |
| Chassis Dimensions     | 437 x 43 x 503mm |

*Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:*

|                                                                      |                                                                                     |                                                |
|----------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------|
| Product SKUs                                                         | Motherboard (for CSE-813MTQ-350CB)                                                  |                                                |
| CSE-813MTQ-350CB • SuperChassis 813MTQ-350CB (Black)                 | <a href="#">A1SAM-2550F</a>                                                         | <a href="#">A1SAM-2750F</a>                    |
|                                                                      | <a href="#">A1SRM-2558F</a>                                                         | <a href="#">A1SRM-2758F</a>                    |
| Form Factor                                                          | <a href="#">A1SRM-LN5F-2358</a>                                                     | <a href="#">A1SRM-LN7F-2358</a>                |
| 1U chassis support for max. motherboard size - 12" x 10" ATX         | <a href="#">A1SRM-LN7F-2758</a>                                                     | <a href="#">H8SCM</a>                          |
|                                                                      | <a href="#">H8SCM-F</a>                                                             | <a href="#">H8SGL</a>                          |
| Processor Support                                                    | <a href="#">H8SGL-F</a>                                                             | <a href="#">H8SML-7</a>                        |
| Supports dual, single Intel® / AMD processors                        | <a href="#">H8SML-7F</a>                                                            | <a href="#">H8SML-i</a>                        |
|                                                                      | <a href="#">H8SML-iF</a>                                                            | <a href="#">X10SDV-2C-7TP4F</a>                |
| Dimensions                                                           | <a href="#">X10SDV-4C-7TP4F</a>                                                     | <a href="#">X10SDV-7TP4F</a>                   |
| Height • 1.7" (43mm)                                                 | <a href="#">X10SDV-7TP8F</a>                                                        | <a href="#">X10SL7-F</a>                       |
| Width • 17.2" (437mm)                                                | <a href="#">X10SLH-F</a>                                                            | <a href="#">X10SLL+-F</a>                      |
| Depth • 19.8" (503mm)                                                | <a href="#">X10SLL-F</a>                                                            | <a href="#">X10SLM+-F</a>                      |
| Packaging • 23.4" (W) x 8.5" (H) x 29.7" (L)                         | <a href="#">X10SLM+-LN4F</a>                                                        | <a href="#">X10SLM-F</a>                       |
| Gross Weight • 31 lbs (14.1kg)                                       | <a href="#">X11SSH-CTF</a>                                                          | <a href="#">X11SSH-F</a>                       |
| Available Colors • Black                                             | <a href="#">X11SSH-LN4F</a>                                                         | <a href="#">X11SSH-TF</a>                      |
|                                                                      | <a href="#">X11SSL</a>                                                              | <a href="#">X11SSL-CF</a>                      |
| Expansion Slots                                                      | <a href="#">X11SSL-F</a>                                                            | <a href="#">X11SSL-nF</a>                      |
| 1x full-height, half-length PCI expansion slot (Riser Card Required) | <a href="#">X11SSM</a>                                                              | <a href="#">X11SSM-F</a>                       |
|                                                                      | <a href="#">X11SSZ-F</a>                                                            | <a href="#">X11SSZ-QF</a>                      |
| Drive Bays                                                           | <a href="#">X11SSZ-TLN4F</a>                                                        | <a href="#">X8DTL-3</a>                        |
| Hot-swap • 4x 3.5" Hot-swap SAS / SATA drive bays                    | <a href="#">X8DTL-3F</a>                                                            | <a href="#">X8DTL-6F</a>                       |
| • SAS or enterprise SATA HDD only recommended                        | <a href="#">X8DTL-i</a>                                                             | <a href="#">X8DTL-iF</a>                       |
|                                                                      | <a href="#">X8Si6-F</a>                                                             | <a href="#">X9DBL-3</a>                        |
| SAS / SATA Backplane                                                 | <a href="#">X9DBL-3F</a>                                                            | <a href="#">X9DBL-i</a>                        |
| 1x SAS / SATA Backplane                                              | <a href="#">X9DBL-iF</a>                                                            | <a href="#">X9SCL-LN4</a>                      |
|                                                                      | <a href="#">X9SCL</a>                                                               | <a href="#">X9SCL+-F</a>                       |
| Peripheral Drives                                                    | <a href="#">X9SCL-F</a>                                                             | <a href="#">X9SCM</a>                          |
| DVD-ROM • Slim DVD-ROM drive (Optional)                              | <a href="#">X9SCM-F</a>                                                             | <a href="#">X9SCM-iF</a>                       |
|                                                                      | <a href="#">X9SKV-1105</a>                                                          | <a href="#">X9SKV-1125</a>                     |
| Front Panel                                                          | <a href="#">X9SKV-B915</a>                                                          | <a href="#">X9SRH-7F</a>                       |
| Buttons • Power On/Off button                                        | <a href="#">X9SRH-7TF</a>                                                           | <a href="#">X9SRi</a>                          |
| • System Reset button                                                | <a href="#">X9SRi-3F</a>                                                            | <a href="#">X9SRi-F</a>                        |
| LEDs • Power LED                                                     | Server(s) for SC813MTQ-350CB                                                        |                                                |
| • Hard drive activity LED                                            | <a href="#">5017C-MTF</a>                                                           | <a href="#">5018D-MTF</a>                      |
| • 2x Network activity LEDs                                           | <a href="#">5018D-MTLN4F</a>                                                        | <a href="#">5018R-M</a>                        |
| • System Overheat LED                                                | <a href="#">6017B-MTLF</a>                                                          | <a href="#">6016T-MTLF</a>                     |
| Ports • 2x Front USB Ports                                           | System Cooling                                                                      |                                                |
| • 1x Serial COM Port                                                 | Fans                                                                                | • 4x 4cm 12,500 RPM PWM fans                   |
|                                                                      | Operating Environment (System)                                                      |                                                |
|                                                                      | Operating Temperature Range                                                         | • 5°C ~ 35°C (41°F ~ 95°F)                     |
|                                                                      | Non-Operating Temperature Range                                                     | • -40°C ~ 60°C (-40°F ~ 140°F)                 |
|                                                                      | Operating Relative Humidity Range                                                   | • 8% ~ 90% (non-condensing)                    |
|                                                                      | Non-Operating Relative Humidity Range                                               | • 5% - 95% (non-condensing)                    |
|                                                                      | Power Supply                                                                        |                                                |
|                                                                      | 350W AC power supply w/ PFC                                                         |                                                |
|                                                                      | AC Voltage                                                                          | • 100-240 V, 50-60 Hz, 4.2-1.8 Amp             |
|                                                                      | +5V                                                                                 | • 18 Amp                                       |
|                                                                      | +5V standby                                                                         | • 3 Amp                                        |
|                                                                      | +12V                                                                                | • 29 Amp                                       |
|                                                                      | +3.3V                                                                               | • 15 Amp                                       |
|                                                                      |  |                                                |
|                                                                      | Certification                                                                       | Gold Certified [ <a href="#">Test Report</a> ] |
|                                                                      | Regulatory (Power Supply)                                                           |                                                |
|                                                                      | Power Supply                                                                        | • USA - UL listed, FCC                         |
|                                                                      | Safety / EMC                                                                        | • Canada - CUL listed                          |
|                                                                      |                                                                                     | • Europe/CE Mark                               |
|                                                                      |                                                                                     | • EN 60950/IEC 60950-Compliant                 |

Strona firmowa produktu:  
<https://www.superstorage.pl/supermicro-superchassis-sc813mtq-350cb-1u-4xlf-fix-psu-p-2189.html>