Supermicro SuperChassis SC743TQ-865B-SQ Tower/4U 8xLFF FIX PSU

Kod producenta: CSE-743TQ-865B-SQ

Chassis Form Factor	Tower/4U
# of 3.5 hot-swap bays	8
Power Supply	Fixed
PSU Wattage	865W
PSU Certification	80+

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-743TQ-865B-SQ	• SuperChassis 743TQ-865B-SQ (**Black**)

Form Factor

4U chassis support for max. motherboard size - 12" x 13" E-ATX

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Width	• 7.0" (178mm)
Height	• 17.8" (452mm)
Depth	• 25.5" (648mm)
Gross Weight	• 56 lbs (25.4kg)
Available Colors	• Black

Expansion Slots

7x Full-height, Full-length PCI expansion slots

Drive Bays

Hot-swap	• 8x 3.5" SAS / SATA Hot-swap Drive Bays • SAS or enterprise SATA HDD only recommended
Peripheral Bay(s)	• 2x 5.25" Peripheral Drive Bay • 1x 5.25" Bay for 3.5" Device • Drive Bays are 90° Rotatable

SAS / SATA Backplane

SAS / SATA Hard Drive Backplane w/AMI MG9072

Front Panel

Buttons	• Power On/Off button • System Reset button
LEDs	• Power LED • Hard drive activity LED • 2x Network activity LEDs • System Overheat LED • Power Fail LED
Ports	• 2x USB Ports

Motherboard (for CSE-743TQ-865B-SQ)

C7B75	C7H170-M
C7Z87	C7Z87-OCE
H8SCM	H8SCM-F
H8SGL	H8SGL-F
X10DAL-i	X10SAE
X10SLA-F	X10SLH-F
X10SLL-F	X10SLL-SF
X10SLM+-F	X10SLM+-LN4F
X10SLM-F	X8DA3
X8DAi	X8DAL-3
X8DAL-i	X8DT3
X8DT3-F	X8DT3-LN4F
X8DT6	X8DT6-F
X8DTE	X8DTE-F
X8DTH-6F	X8DTH-i
X8DTH-iF	X8DTi
X8DTi-F	X8DTi-LN4F
X8DTL-3	X8DTL-3F
X8DTL-6	X8DTL-6F
X8DTL-I	X8DTL-IF
X8SIE	X8SIE-F
X8SIL	X8SIL-F
X9DAL-3	X9DAL-i
X9SAE	X9SAE-V
X9SCI-LN4	X9SRA
X9SRE	X9SRE-3F
X9SRE-F	X9SRi
X9SRi-3F	X9SRi-F
X9SRL-F	

System Cooling

Fans	• 2x Super Quiet PWM Chassis Fans • 1x Super Quiet Rear Fan

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature Range	• 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range	• -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range	• 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range	• 5% - 95% (non-condensing)

Power Supply

865W AC power supply (cooling-redundant) w/ PFC

AC Voltage	• 100 - 240V, 50-60Hz, 12-6 Amp
+5V standby	• 6.5 Amp
+12V	• 70 Amp
+5V	• 30 Amp
+3.3V	• 30 Amp
-12V	• 1 Amp
Certification	**Certified**

Regulatory (Power Supply)

Power Supply Safety / EMC	• USA - UL listed, FCC • Canada - CUL listed • Germany - TUV Certified • Europe/CE Mark • EN 60950/IEC 60950-Compliant • CB report ready

Strona firmowa produktu:
https://www.superstorage.pl/supermicro-superchassis-sc743tq-865b-sq-tower4u-8xlff-fix-psu-p-2194.html