

Supermicro SuperChassis SC745TQ-R920B Tower/4U 8xLFF RED PSU

Kod producenta: CSE-745TQ-R920B



Chassis Form Factor	Tower/4U
# of 3.5 hot-swap bays	8
Power Supply	Redundant
PSU Wattage	920W
PSU Certification	80+ Platinum

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs	Motherboard (for CSE-745TQ-R920B)	
CSE-745TQ-R920B • SuperChassis 745TQ-R920B (Black)		
Form Factor	C7B75	C7Z87
Tower / 4U chassis support for motherboard size - 13.68" x 13" (34.7cm x 33cm), ATX, E-ATX	C7Z87-OCF	H8DCL-6
	H8DCL-6F	H8DCL-i
	H8DCL-iF	H8SCM
	H8SCM-F	H8SGL
	H8SGL-F	X10DAC
Processor Support	X10DAi	X10DAX
Supports dual, single Intel® / AMD processors	X10DRC-LN4+	X10DRC-T4+
	X10DRI-LN4+	X10DRI-T4+
Dimensions	X10SAE	X10SAT
Height • 17.8" (452mm)	X10SL7-F	X10SLA-F
Width • 7.0" (178mm)	X10SLH-F	X10SLL+-F
Depth • 25.5" (648mm)	X10SLI-F	X10SLI-S
Gross Weight • 62 lbs (28 kg)	X10SLI-SF	X10SLM+-F
Available Colors • Black	X10SLM+-LN4F	X10SLM-F
	X8DA3	X8DA6
	X8DAE	X8DAH+
	X8DAH+-F	X8DAi
Expansion Slots	X8DAL-3	X8DAL-i
7x PCI expansion slots	X8DT3	X8DT3-F
	X8DT3-LN4F	X8DT6
Drive Bays	X8DT6-F	X8DTE
	X8DTE-F	X8DTH-6F
	X8DTH-i	X8DTH-iF
	X8DTi	X8DTi-F
Hot-swap	X8DTi-LN4F	X8DTL-3
• 8x 3.5" Hot-swap SAS/SATA Drive Bays	X8DTL-3F	X8DTL-6
• SAS or enterprise SATA HDD only recommended	X8DTL-6F	X8DTL-i
Peripheral Bay(s)	X8DTL-iF	X8DTN+
• 2x 5.25" Peripheral Drive Bay	X8DTN+-F	X8DTN+-F-LR
• 1x 5.25" Bay that fits 3.5" bay devices	X8DTN+-LR	X9DA7
SAS / SATA Backplane	X9DAE	X9DAi
	X9DB3-F	X9DB3-TPF
SAS / SATA Hard Drive Backplane with SES2	X9DBi-F	X9DBi-TPF
	X9DR3-F	X9DR3-LN4F+
Front Panel	X9DRH-7F	X9DRH-7TF
	X9DRH-iF	X9DRH-iF-NV
Buttons	X9DRH-iTF	X9DRi-F
• Power On/Off button	X9DRI-LN4F+	X9SAE
• System Reset button	X9SAE-V	X9SCL-LN4
• Power LED	X9SCL	X9SCL+-F
• Hard drive activity LED	X9SCL-F	X9SCM
• 2x Network activity LEDs	X9SCM-F	X9SCM-iiF
• System Overheat LED	X9SRA	X9SRE
• Power Fail LED	X9SRE-3F	X9SRE-F
Ports	X9SRi	X9SRi-3F
• 2x USB Ports	X9SRi-F	
	Server(s) for SC745TQ-R920B	
	7047R-3RF4+	7047R-72RFT
	7047R-TRF	7047R-72RF
	7048R-TR	7048R-TRT
	7048R-C1R4+	7048R-C1RT
	7048R-C1R	
	System Cooling	
		• 3x 5000 RPM Hot-swap PWM Cooling Fans
Fans		• 2x 5000 RPM Hot-swap Rear Exhaust PWM Fans
	System Monitoring	
	Chassis intrusion switch	
	Operating Environment (System)	
	Operating Temperature Range	• 5°C ~ 35°C (41°F ~ 95°F)
	Non-Operating Temperature Range	• -40°C ~ 60°C (-40°F ~ 140°F)
	Operating Relative Humidity Range	• 8% ~ 90% (non-condensing)
	Non-Operating Relative Humidity Range	• 5% - 95% (non-condensing)
	Power Supply with Power Distributor	
	920W high-efficiency (94%+) AC-DC Redundant power supplies with PMBus and I2C	
	AC Input	• 100-240 V, 50-60 Hz, 11-4.5 Amp
	DC Output	• 4 Amp @ +5V standby
		• 75 Amp @ +12V
	With Power	• +5V: 30 Amp
	Safety / EMC	• +3.3V: 24 Amp
	Distributor	• -12V: 0.6 Amp
	Certification	Platinum Certified [Test Report]
	Regulatory (Power Supply)	
		• USA - UL listed, FCC
		• Canada - CUL listed
	Power Supply	• China - CCC Mark
	Safety / EMC	• Europe/CE Mark
		• Germany - TÜV Certified

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc745tq-r920b-tower4u-8xlff-red-psu-p-2195.html>