

Supermicro SuperChassis SC813MFTQC-R407CB 1U 4xLFF RED PSU

Kod producenta: CSE-813MFTQC-R407CB



Chassis Form Factor	Rack 1U
# of 3.5 hot-swap bays	4
Power Supply	Redundant
PSU Wattage	400W
PSU Certification	80+ Platinum
Chassis Dimensions	437 x 43 x 503mm

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

• SuperChassis

CSE-813MFTQC-R407CB 813MFTQC-R407CB (black)

Form Factor

1U 1U chassis for motherboard support size 12" x 10", ATX 12" x 10", Micro ATX 9.6" x 8.6"

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height	1.7" (43mm)
Width	17.2" (437mm)
Depth	19.85" (503mm)
Gross Weight	33.5 lb (15.2 kg)
Packaging	23.4" (W) x 8.5"(H) 29.7" (L)
Available Color	black

Expansion Slots

• 1 full-height & full-length expansion slot(s)

Drive Bays

Internal Bay	• 4x 3.5" hot-swap SAS/SATA drive bay with SES2
--------------	---

Backplane

1U SAS/SATA Backplane with SES2 support

Peripheral Drives

• 1 Optional slim DVD-ROM drive bay

• 1 Optional USB + COM port tray

Front Panel

Buttons	• Power On/Off button
	• System Reset Button
	• 2 Network Activity LEDs
LEDs	• Fan Fail/System Over Heat LED
	• HDD activity LED
	• Power Status LED

Motherboard (for CSE-813MFTQC-R407CB)

[X10SRM-F](#) [X10SRM-TF](#)

System Cooling

Fans

- 4x 40x28mm PWM fan
- Optional 2x fans for AOC cooling

Operating Environment (System)

Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)

Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)

Operating Relative Humidity Range • 8% ~ 90% (non-condensing)

Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

AC/DC240V Input Redundant Power Supplies

400W 1U Redundant Power Supplies with PMbus

Total Output Power • 400W

Dimension (W x H x L) • 54.5 x 40 x 220 mm

• 100 - 240Vac / 6.0 - 3.0A / 50-60Hz

Input • 200 - 240Vdc / 3.4 - 3.2A (CCC Only)

+12V • Max: 33A / Min: 0.5A

+5V sb • Max: 3A / Min: 0A

Output Type • Gold Finger Connector Mating with Molex 45984-4343

Certification

 **Platinum Level Certified**

[[Test Report](#)]

Regulatory (Power Supply)

Power Supply Safety / EMC

- USA - UL listed, FCC
- Canada - CUL listed
- Germany - TUV Certified
- Europe/CE Mark
- EN 50950/IEC 50950-Compliant

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc813mftqc-r407cb-1u-4xlff-red-psu-p-2242.html>