

Supermicro SuperChassis SC813MFTQC-505CB 1U 4xLFF FIX PSU

Kod producenta: CSE-813MFTQC-505CB



Chassis Form Factor	Rack 1U
# of 3.5 hot-swap bays	4
Power Supply	Fixed
PSU Wattage	500W
PSU Certification	80+ Platinum
Chassis Dimensions	437 x 43 x 503mm

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-813MFTQC-505CB • SuperChassis
813MFTQC-505CB (black)

Form Factor

1U chassis for motherboard support size 12" x 10",
9.6" x 9.6"

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height 1.7" (43mm)
Width 17.2" (437mm)
Depth 19.85" (503mm)
Gross Weight 1b (kg)
Packaging 23.4" (W) x 8.5"(H) 29.7" (L)
Available Color black

Expansion Slots

1 full-height & full-length expansion slot(s)

Drive Bays

Internal Bay • 4x 3.5" hot-swap SAS/SATA drive bay with SES2

Front Panel

Buttons • Power On/Off button
• System Reset Button
• 2 Network Activity LEDs
LEDs • Fan Fail/System Over Heat LED
• HDD activity LED
• Power Status LED

Motherboard (for CSE-813MFTQC-505CB)

X10DRL-C	X10DRL-CT
X10DRL-iT	X11SSH-CTF
X11SSH-F	X11SSH-LN4F
X11SSH-TF	X11SSi-LN4F
X11SSL	X11SSL-CF
X11SSL-F	X11SSL-nF
X11SSM	X11SSM-F

System Cooling

Fans • 4x 40x28mm PWM fan
• Optional 2x 40x28mm PWM fan

Operating Environment (System)

Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range • 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

Power Supply

500W High-Efficiency Power Supply w/PMBus 1.2, I²C, and PFC
AC Input • 100-240V, 50-60Hz, 6.6A max
• +3.3V: 12A
• +5V: 15A
DC Output • +5V standby: 3A
• +12V: 41A
• -12V: 0.2A

Certification  **Platinum Certified**

Regulatory (Power Supply)

Power Supply Safety / EMC • USA - UL listed, FCC
• Canada - CUL listed
• Germany - TUV Certified
• Europe/CE Mark
• EN 50950/IEC 50950-Compliant

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc813mftqc-505cb-1u-4xlf-fix-psu-p-2244.html>