

# Supermicro SuperChassis SC813MFTQ-441CB 1U 4xLFF FIX PSU

Kod producenta: CSE-813MFTQ-441CB



|                        |                  |
|------------------------|------------------|
| Chassis Form Factor    | Rack 1U          |
| # of 3.5 hot-swap bays | 4                |
| Power Supply           | Fixed            |
| PSU Wattage            | 440W             |
| PSU Certification      | 80+ Platinum     |
| Chassis Dimensions     | 437 x 43 x 503mm |

*Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:*

Product SKUs

CSE-813MFTQ-441CB • SuperChassis 813MFTQ-441CB (Black)

Form Factor

1U chassis support for max. motherboard size  
- Micro ATX9.6"x 9.6" or ATX 12" x 10"

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

- Height • 1.7" (43mm)
- Width • 17.2" (437mm)
- Depth • 19.8" (503mm)
- Packaging • 23.4" (W) x 8.5" (H) x 29.7" (L)
- Gross Weight • 31 lbs (14.1kg)
- Available Colors • Black

Expansion Slots

1x full-height expansion slot (Riser card required)

Drive Bays

- Hot-swap • 4x 3.5" Hot-swap SAS / SATA drive bays
- SAS or enterprise SATA HDD only recommended

SAS / SATA Backplane

1x SAS / SATA Backplane

Peripheral Drives

- Others • Front USB/COM tray in slim DVD bay (Optional)

Front Panel

- Buttons • Power On/Off button
- System Reset button
- Power LED
- LEDs • Hard drive activity LED
- 2x Network activity LEDs
- System Overheat LED

Motherboard (for CSE-813MFTQ-441CB )

- [X10DRL-C](#)
- [X10DRL-CT](#)
- [X10DRL-i](#)
- [X10DRL-iT](#)
- [X10SRH-CF](#)
- [X10SRH-CLN4F](#)
- [X10SRi-F](#)
- [X10SRL-F](#)

Server(s) for SC813MFTQ-441CB

- [6017R-MTLF](#)
- [6018R-MT](#)

System Cooling

- Fans • 4x 4cm high performance fans
- 2x additional fans optional ; 6x fans total maximum

Operating Environment (System)

- Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F) Range
- Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F) Range
- Operating Relative Humidity • 8% ~ 90% (non-condensing) Range
- Non-Operating Relative Humidity • 5% - 95% (non-condensing) Range

Power Supply

- 440W/480W High-Efficiency Power Supply w/PMBus 1.2, I2C, and PFC
- AC Input • 100-140V, 50-60Hz, 5.5-4A
- 180-240V, 50-60Hz, 3.5-2.5A
- +3.3V: 15A
- +5V: 18A
- DC Output • +5V standby: 3A
- +12V: 35.8A at 100-140Vac
- 39.1A at 180-240Vac

Certification  **Platinum Certified**  
[ [Test Report](#) ]

Regulatory (Power Supply)

- Power Supply • USA - UL listed, FCC
- Safety / EMC • Canada - CUL listed
- Europe/CE Mark
- EN 60950/IEC 60950-Compliant

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc813mftq-441cb-1u-4xlff-fix-psu-p-2248.html>