

Supermicro SuperChassis SC815TQ-R654CB 1U 4xLFF RED PSU

Kod producenta: CSE-815TQ-R654CB



Chassis Form Factor	Rack 1U
# of 3.5 hot-swap bays	4
Power Supply	Redundant
PSU Wattage	650W

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-815TQ-R654CB • SuperChassis
815TQ-R654CB (**Black**)

Form Factor

1U chassis support for max. motherboard size - 12" x 13"

Processor Support

Supports dual Intel® / AMD processors

Dimensions

- Height • 1.7" (43mm)
- Width • 17.2" (437mm)
- Depth • 25.6" (650mm)
- Gross Weight • 36 lbs (16.4kg)
- Package • 23.5" x 8.5" x 33.7"
- Available Colors • Black

Expansion Slots

- 1x full-height, full-length PCI expansion slot (Riser Card Required)

Drive Bays

- Hot-swap • 4x 3.5" SAS / SATA Hot-swap drive trays
- SAS or enterprise SATA HDD only recommended

SAS / SATA Backplane

1x 1U SAS / SATA backplane

Peripheral Drives

- DVD-ROM • Slim DVD-ROM drive (optional)

Front Panel

- Buttons • Power On/Off button
- System Reset button
- LEDs • Power LED
- Hard drive activity LED
- 2x Network activity LEDs
- System Overheat LED
- Ports • 2x USB & DB9 COM port tray
- (Optional - in place of floppy drive)

System Cooling

- Fans • 4x 4cm Counter-rotating PWM fans

Operating Environment (System)

- Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)
- Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)
- Operating Relative Humidity Range • 8% ~ 90% (non-condensing)
- Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

-48Vdc Input Redundant Power Supplies

650W Redundant Power Supplies with SMBus

- Total Output Power • 650W
- Dimension (W x H x L) • 54.5 x 40 x 320 mm
- DC Input • -44Vdc to -72Vdc / 20A Max
- +12V • Max: 53.28A / Min: 0A
- +5V sb • Max: 3A / Min: 0A
- Output Type • Gold Finger Connector Mating with Molex 45984-4343
- Certification • UL/cUL/CB/TUV/CCC/CE

Regulatory (Power Supply)

- USA - UL listed, FCC
- Canada - CUL listed
- Power Supply • China - CCC Mark
- Safety / EMC • Europe/CE Mark
- EN 60950/IEC 60950-Compliant
- Germany - TUV Certified

Strona firmowa produktu:

