Supermicro SuperChassis SC815TQC-R706WB 1U 4xLFF RED PSU

Part number: CSE-815TQC-R706WB

Chassis Form Factor	Rack 1U
# of 3.5 hot-swap bays	4
Power Supply	Redundant
PSU Wattage	750 W
PSU Certification	80+ Platinum

Product SKUs

CSE-815TQC-R706WB	• SuperChassis 815TQC-R706WB (black)

Form Factor

1U Chassis optimized for WIO (W series) motherboards

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height	1.7" (43mm)
Width	17.2" (437mm)
Depth	25.6" (650mm)
Gross Weight	36 lb (16.33 kg)
Packaging	23.5'' (W) x 8.5''(H) 33.7'' (L)
Available Color	black

Expansion Slots

•2 full-height & full-length expansion slot(s)
•1 low-profile expansion slot(s)

Drive Bays

Internal Bay	• 4x 3.5" hot-swap SAS/SATA • SAS or enterprise SATA HDD only recommended

Backplane

•1U SAS/SATA Backplane with SES2 support
• SAS3 12Gb/s support

Front Panel

Buttons	• Power On/Off button • System Reset Button • Unit Identification (UID) button
LEDs	• 2 Network Activity LEDs • Fan Fail/System Over Heat LED • HDD activity LED • Power Status LED • Unit Identification (UID) LED

System Cooling

Fans	4x 40x56mm counter-rotation PWM fan

Operating Environment (System)

Operating Temperature Range	• 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range	• -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range	• 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range	• 5% - 95% (non-condensing)

Power Supply

400W SuperCompact Short-depth AC-DC high-efficiency power supply with PMBus and I2C

AC Voltage	• 400W: 100-240 V, 50-60 Hz, 6-3 Amp
DC Output +5V standby	• 3 Amp
DC Output +5V standby	• 3 Amp
With Power Distributor	• +5V: 25 Amp • +3.3V: 25 Amp • -12V: 0.6 Amp

Regulatory (Power Supply)

Power Supply Safety / EMC	• USA - UL listed, FCC • Canada - CUL listed • Germany - TUV Certified • Europe/CE Mark • EN 60950/IEC 60950-Compliant

Visit us for more info:
https://www.superstorage.pl/supermicro-superchassis-sc815tqc-r706wb-1u-4xlff-red-psu-p-2254.html