

Supermicro SuperChassis SC815TQC-R504CB 1U 4xLFF RED PSU

Kod producenta: CSE-815TQC-R504CB



Chassis Form Factor	Rack 1U
# of 3.5 hot-swap bays	4
Power Supply	Redundant
PSU Wattage	500W
PSU Certification	80+ Platinum
Uwagi	SAS3 12Gb/s Support

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs		System Cooling	
CSE-815TQC-R504CB • SuperChassis 815TQC-R504CB (black)		Fans	3x 40x56mm counter-rotation PWM fan
Form Factor		Operating Environment (System)	
1U chassis support for max. motherboard size - 12" x 13"		Operating Temperature Range	• 5°C ~ 35°C (41°F ~ 95°F)
Processor Support		Non-Operating Temperature Range	• -40°C ~ 60°C (-40°F ~ 140°F)
Supports dual, single Intel® / AMD processors		Operating Relative Humidity Range	• 8% ~ 90% (non-condensing)
Dimensions		Non-Operating Relative Humidity Range	• 5% - 95% (non-condensing)
Height	1.7" (43mm)	Power Supply with Power Distributor	
Width	17.2" (437mm)	500W high-efficiency (94+%) power supply w/ PMBus	
Depth	25.6" (650mm)	With Power Distributor	• +5V: 25 Amp • +3.3V: 12 Amp • -12V: 0.6 Amp
Gross Weight	36 lb (16.33 kg)	Certification	 Platinum Certified [Test Report]
Packaging	23.5" (W) x 8.5"(H) 33.7" (L)		
Available Color	black	Regulatory (Power Supply)	
Expansion Slots		Power Supply Safety / EMC	• USA - UL listed, FCC • Canada - CUL listed • Germany - TUV Certified • Europe/CE Mark • EN 60950/IEC 60950-Compliant
1 full-height & full-length expansion slot(s)			
Drive Bays			
Internal Bay	• 4x 3.5" hot-swap SAS/SATA • SAS or enterprise SATA HDD only recommended		
Backplane			
• 1U SAS/SATA Backplane with SES2 support • SAS3 12Gb/s support			
Front Panel			
Buttons	• Power On/Off button • System Reset Button • 2 Network Activity LEDs • Fan Fail/System Over Heat LED		
LEDs	• HDD activity LED • Power Status LED • Unit Identification (UID) LED		

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc815tqc-r504cb-1u-4xlff-red-psu-p-2256.html>