

Supermicro SuperChassis SC815TQ-R706WB 1U 4xLFF RED PSU

Kod producenta: CSE-815TQ-R706WB



Chassis Form Factor	Rack 1U
# of 3.5 hot-swap bays	4
Power Supply	Redundant
PSU Wattage	750W
PSU Certification	80+ Platinum

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-815TQ-R706WB • SuperChassis 815TQ-R706WB (black)

Form Factor

- 1U chassis for motherboard support size of Proprietary 12" x 13"
- Optimized for WIO (W series) motherboards

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

- Height** 1.7" (43mm)
- Width** 17.2" (437mm)
- Depth** 25.6" (650mm)
- Gross Weight** 36 lb (16.33 kg)
- Packaging** 23.5" (W) x 8.5" (H) 33.7" (L)
- Available Color** black
- 1x Low-profile Expansion Slot (Riser Card Required)

Expansion Slots

- 2x Full-height Expansion Slots (Riser Card Required)

Drive Bays

- Hot-Swap** • 4x 3.5" hot-swap SAS/SATA
- SAS or enterprise SATA HDD only recommended

Backplane

- 1U SAS/SATA Backplane with SES2 support

Peripheral Drives

- DVD ROM** • Slim DVD-ROM drive (optional)

Front Panel

- Buttons** • Power On/Off button
- System Reset Button
- Unit Identification (UID) button
- 2 Network Activity LEDs
- Fan Fail/System Over Heat LED
- LEDs** • HDD activity LED
- Power Status LED
- Unit Identification (UID) LED

Motherboard (for CSE-815TQ-R706WB)

- [X10DRW-E](#) [X10DRW-ET](#)
- [X10DRW-i](#) [X10DRW-iT](#)
- [X10DRW-N](#) [X10DRW-NT](#)
- [X10SRW-F](#)

System Cooling

- Fans** 4x 40x56mm counter-rotation PWM fan

Operating Environment (System)

- Operating Temperature Range** • 5°C ~ 35°C (41°F ~ 95°F)
- Non-Operating Temperature Range** • -40°C ~ 60°C (-40°F ~ 140°F)
- Operating Relative Humidity Range** • 8% ~ 90% (non-condensing)
- Non-Operating Relative Humidity Range** • 5% - 95% (non-condensing)

AC/DC240V Input Redundant Power Supply

- 700W/750W Redundant Power Supplies with PMBus
- Total Output Power** • 700W/750W
- Dimension (W x H x L)** • 54.5 x 40 x 320 mm
- Input** • 100 - 140Vac / 8 - 6A / 50-60Hz
- 200 - 240Vac / 4.5 - 3.8A / 50-60Hz
- 200 - 240Vdc / 4.5 - 3.8A (CCC Only)
- Max: 58A / Min: 0.5A (100 - 140Vac)
- Max: 62A / Min: 0.5A (200 - 240Vac)
- Max: 62A / Min: 0.5A (200 - 240Vdc) (CB/CCC Only)
- +12V** • Max: 3A / Min: 0A
- +5V sb** • Max: 3A / Min: 0A
- Output Type** • Gold Finger Connector Mating with Molex 45984-4343

- Certification**  **Platinum Certified**
- [\[Test Report \]](#)

Regulatory (Power Supply)

- Power Supply Safety / EMC** • USA - UL listed, FCC
- Canada - CUL listed
- Germany - TUV Certified
- Europe/CE Mark
- EN 60950/IEC 60950-Compliant

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc815tq-r706wb-1u-4xlff-red-psu-p-2258.html>