

Supermicro SuperChassis SC512F-410B 1U 1xLFF FIX PSU

Kod producenta: CSE-512F-410B



Chassis Form Factor	Rack 1U
# of 3.5 fixed bays	1
Power Supply	Fixed
PSU Wattage	410W



Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs	System Cooling
CSE-512F-410B • SuperChassis 512F-410B (Black)	Fans • 3x 4cm 4-pin PWM Fans
Form Factor	Operating Environment (System)
14.5" Mini 1U chassis support for max. motherboard size - 12" x 10" ATX	Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)
Processor Support	Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)
Supports dual, single Intel® / AMD processors	Operating Relative Humidity Range • 8% ~ 90% (non-condensing)
Dimensions	Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)
Height • 1.7" (43mm)	-48Vdc Input Power Supply
Width • 17.2" (437mm)	410W 1U Multiple Output Power Supply
Depth • 14.5" (369mm)	Total Output Power • 410W
Gross Weight • 14 lbs (6.4kg)	Note: +5V and +3.3V Total output max: 180W
Available Color • Black	Dimension (W x H x L) • 100 x 40 x 240 mm
Expansion Slot	DC Input • -36Vdc to -72Vdc / 17A Max
1x full-height half-length expansion slot (Riser Card Required)	+12V • Max: 32A / Min: 1A
Drive Bay	+5V • Max: 35A / Min: 1A
Internal Bay • 1x 3.5" internal drive bay SAS or enterprise SATA HDD only recommended	+3.3V • Max: 20A / Min: 1A
Peripheral Drives	-12V • Max: 20A / Min: 1A
DVD-ROM • TEAC Slim DVD-ROM drive	+5V sb • Max: 0.5A / Min: 0.1A
Front Panel	Output Type • 24Pin ATX Cable Output
Buttons • Power On/Off button • Reset button	Certification • UL/cUL/TUV/CB/CE
LEDs • Power LED • Hard drive activity LED	Regulatory (Power Supply)
• 2x Network activity LEDs	• USA - UL listed, FCC
• System Overheat LED	• Canada - CUL listed
Ports • 2x USB 2.0 Ports	Power Supply • Germany - TUV Certified
	Safety / EMC • Europe/CE Mark
	• EN 60950/IEC 60950-Compliant
	• CCC

Strona firmowa produktu:
<https://www.superstorage.pl/supermicro-superchassis-sc512f-410b-1u-1x1ff-fix-psu-p-2275.html>