

Supermicro SuperChassis SC826TQ-R800LPB 2U 12xLFF RED PSU

Kod producenta: CSE-826TQ-R800LPB



Chassis Form Factor	Rack 2U
# of 3.5 hot-swap bays	12
Power Supply	Redundant
PSU Wattage	800W

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs	
CSE-826TQ-R800LPV Silver :	• SuperChassis 826TQ-R800LPV (OEM only *)
CSE-826TQ-R800LPB Black :	• SuperChassis 826TQ-R800LPB (OEM only *)

Form Factor	
2U chassis support for max. motherboard size - 13" x 13.68" E-ATX	
Processor Support	
Supports dual, single Intel® / AMD processors	
Dimensions	
Width	17.2" (437mm)
Height	3.5" (89mm)
Depth	25.5" (648mm)
Gross Weight	52 lbs (23.6kg)
Packaging	• 26.7" (W) x 11.4" (H) x 34.5" (L)
Available Colors	Black, Silver (OEM) *

Expansion Slots	
• 7x low-profile full-length expansion slots	

Drive Bays	
Hot-swap	12 x 3.5" SAS / SATA Hot-swap drive trays SAS or enterprise SATA HDD only recommended

Backplane	
2U Direct Attached Backplane, features:	
• 3Gb/6Gb support	
• SES-2 Enclosure Management Support	
• SAS/SATA support	
• 12 SATA connectors	

Front Panel	
Buttons	• Power On/Off button • System Reset button

Motherboard (for CSE-826TQ-R800LPB)	
X8DA3	X8DA6
X8DAE	X8DAi
X8DAL-3	X8DAL-i
X8DT3	X8DT3-F
X8DT3-LN4F	X8DT6
X8DT6-F	X8DTE
X8DTE-F	X8DTH-6F
X8DTH-i	X8DTH-iF
X8DTi	X8DTi-F
X8DTi-LN4F	X8DTN+
X8DTN+-LR	X8SIE
X8SIE-F	X8SIL
X8SIL-F	X8ST3-F

System Cooling	
Fans	3x 80mm 7000 RPM fans

System Monitoring	
Chassis intrusion switch	

Operating Environment (System)	
Operating Temperature Range	• 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range	• -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range	• 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range	• 5% - 95% (non-condensing)

Power Supply and Distributor	
800W (1 + 1) Redundant AC-DC high-efficiency power supply w/ PFC	
AC Voltage	• 100 - 240V, 50-60Hz, 10-4 Amp
+5V standby	• 4 Amp
+12V	• 66 Amp
With Power Distributor	• +5V: 30 Amp • +3.3V: 24 Amp • -12V: 0.6 Amp

Regulatory (Power Supply)	
Power Supply Safety / EMC	• USA - UL listed • Canada - CUL listed • Germany - TUV Certified • EN 60950/IEC 60950-Compliant • CB Report • CCC Certification

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc826tq-r800lpb-2u-12xlff-red-psu-p-2280.html>