

Supermicro SuperChassis SC213LT-600LPB 2U 8xSFF FIX PSU

Kod producenta: CSE-213LT-600LPB



Chassis Form Factor	Rack 2U
# of 2.5 hot-swap bays	8
Power Supply	Fixed
PSU Wattage	600W
PSU Certification	80+ Platinum

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-213LT-600LPB • SuperChassis 213LT-600LPB (black)

Form Factor

2U chassis support for motherboard size - 13.68" x 13", E-ATX and ATX

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Width • 17.2" (437mm)
Height • 3.5" (89mm)
Depth • 24.8" (630mm)
Packaging • 26.5" (W) x 10.5" (H) x 38" (L)
Weight • Gross: 48 lbs / Net: 44 lbs
Available Color • Black

Expansion Slots

• 7x Low-profile expansion slots

Drive Bays

HDD 8x 2.5" Hot-swap SAS/SATA HDD bays for SAS or enterprise SATA HDD only
Peripheral 1x 5.25" peripheral drive bay

SAS Backplane

1x 2U SAS backplane w/ Enclosure Management

Front Panel

Buttons • Power On/Off button
• System Reset button
• Power LED
LEDs • Hard drive activity LED
• 2x Network activity LEDs
• System Information LED
• Power fail LED

Motherboard (for CSE-213LT-600LPB)

H8DCL-6	H8DCL-6F
H8DCL-i	H8DCL-iF
H8SCM	H8SCM-F
X10DAL-i	X10DRL-C
X10DRL-CT	X10DRL-i
X10DRL-iT	X10DRL-LN4
X10SL7-F	X10SLA-F
X10SLH-F	X10SLL+-F
X10SLL-F	X10SLL-S
X10SLL-SF	X10SLM+-F
X10SLM+-LN4F	X10SLM-F
X10SRH-CF	X10SRi-F
X10SRL-F	X9DAL-3
X9DAL-i	X9DBL-3
X9DBL-3F	X9DBL-i
X9DBL-iF	X9DRD-7LN4F
X9DRD-7LN4F-JBOD	X9DRD-EF
X9DRD-iF	X9DRD-LF
X9DRL-3F	X9DRL-7F
X9DRL-EF	X9DRL-iF
X9SCI-LN4	X9SCL
X9SCL+-F	X9SCL-F
X9SCM	X9SCM-F
X9SCM-iF	X9SRE
X9SRE-3F	X9SRE-F
X9SRH-7F	X9SRH-7TF
X9SRi	X9SRi-3F
X9SRi-F	X9SRL-F

System Cooling

Fans 3x 80x38mm high-performance, high-quality PWM fans

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range
Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range
Operating Relative Humidity • 8% ~ 90% (non-condensing)
Range
Non-Operating Relative Humidity • 5% - 95% (non-condensing)
Range

Power Supply

600W High-Efficiency Power Supply w/PMBus 1.2, I²C, PFC, and Digital Switching
AC Input • 100-240V, 50-60Hz, 7.5A max
• +3.3V: 15A
• +5V: 18A
DC Output • +5V standby: 3A
• +12V: 49A
• -12V: 0.5A

Certification 
Platinum Certified
[[Test Report](#)]

Regulatory (Power Supply)

Power Supply Safety / EMC	• USA - UL listed
	• Canada - CUL listed
	• Germany - TUV Certified
	• EN 60950/IEC 60950-Compliant
	• CB Report

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc213lt-600lpb-2u-8xsff-fix-psu-p-2288.html>