

Supermicro SuperChassis SC216E16-R1200UB 2U 24xSFF RED PSU

Kod producenta: CSE-216E16-R1200UB



Chassis Form Factor	Rack 2U
# of 2.5 hot-swap bays	24
Power Supply	Redundant
PSU Wattage	1200W
PSU Certification	80+ Gold
Uwagi	Single Expander SAS2 Backplane

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs		Motherboard (for CSE-216E16-R1200UB)	
CSE-216E16-R1200UB • SuperChassis 216E16-R1200UB (Black)			
Form Factor		H8DGU H8DGU-F	
		X8DT6 X8DT6-F	
		X8DTE X8DTE-F	
• 2U chassis supports max. motherboard size of 13.68" x 13"			
• Optimized for Universal I/O (UIO) motherboard		System Cooling	
Processor Support		Fans	
Supports dual, single Intel® / AMD processors		3x 80mm 7000 RPM hot-swap PWM fans	
Dimensions		System Monitoring	
Width • 17.2" (437mm)		Chassis intrusion switch	
Height • 3.5" (89mm)			
Depth • 24.8" (630mm)		Operating Environment (System)	
Packaging • 26.5" (W) x 10.5" (H) x 38" (L)			
Weight • Net Weight: 35 lbs (15.9kg)		Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)	
Available Color Black		Range	
		Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)	
Expansion Slots		Range	
		Operating Relative Humidity • 8% ~ 90% (non-condensing)	
• 4x Full-height expansion slots (riser card required)		Range	
• 3x Low-profile expansion slots (riser card required)		Non-Operating Relative Humidity • 5% - 95% (non-condensing)	
Drive Bays		Range	
Hot-swap 24x 2.5" SAS / SATA Hot-swap drive trays		Power Supply	
		Redundant 1200W high-efficiency power supply with PMBus	
		AC Input • 1000W Output @ 100-140V, 11.5-8A, 50-60Hz	
		• 1200W Output @ 180-240V, 8-5.5A, 50-60Hz	
		DC Output • 1000W: +12V/83A; +5Vsb/4A	
		• 1200W: +12V/100A; +5Vsb/4A	
		DC Output with PDB • +5V: 50 Amp	
		• +3.3V: 30 Amp	
		• -12V: 0.6 Amp	
Front Panel		Certification	
Buttons • Power On/Off button		Gold Certified	
• System Reset button		[Test Report]	
LEDs • Power LED			
• Hard drive activity LED		Regulatory (Power Supply)	
• 2x Network activity LEDs			
• System Overheat LED		Power Supply Safety / EMC	
• Power fail LED		• USA - UL listed	
		• Canada - CUL listed	
		• Germany - TUV Certified	
		• EN 60950/IEC 60950-Compliant	
		• CB Report	
		• CCC Certification	

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc216e16-r1200ub-2u-24xsff-red-psu-p-2305.html>

Copyright ©2024 www.superstorage.pl | czwartek, 02 maj 2024

Strona: 2 / 3

