

Supermicro SuperChassis SC216BE26-R1K28WB 2U 24xSFF RED PSU

Kod producenta: CSE-216BE26-R1K28WB



Chassis Form Factor	Rack 2U
# of 2.5 hot-swap bays	24
Power Supply	Redundant
PSU Wattage	1280W
PSU Certification	80+ Platinum
Uwagi	Dual Expander SAS2 Backplane

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs



CSE-216BE26-R1K28WB • SuperChassis 216BE26-R1K28WB
(Black)

Form Factor



2U chassis support for motherboard size
- 13.68" x 13", E-ATX and ATX

Processor Support



Supports dual, single Intel® / AMD processors

Dimensions



- | | |
|-----------|--|
| Width | • 17.2" (437mm) |
| Height | • 3.5" (89mm) |
| Depth | • 24.8" (630mm) |
| Packaging | • 26.5" (W) x 10.5" (H) x 38" (L) |
| Weight | • Net Weight: 35 lbs (15.9kg)
• Gross Weight: 57 lbs (25.9kg) |

Available Color Black

Expansion Slots



- 7x low-profile expansion slots

Drive Bays



Hot-swap 24x 2.5" SAS / SATA Hot-swap drive trays
SAS or enterprise SATA HDD only
recommended

Backplane



SAS2 Expander Backplane, features:

- Scalability through cascading
- 6Gb SAS2/SATA3 HDD support
- Inband SES-2 Enclosure Management
- Single input/output SFF 8087 connectors

Front Panel



Buttons

- Power On/Off button
- System Reset button

LEDs

- Power LED
- Hard drive activity LED
- 2x Network activity LEDs
- System Overheat LED
- Power fail LED



System Cooling



Fans 3x 80mm 7000 RPM hot-swap PWM fans

System Monitoring



Chassis intrusion switch



Operating Environment (System)



- Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range
- Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range
- Operating Relative Humidity • 8% ~ 90% (non-condensing)
Range
- Non-Operating Relative Humidity • 5% - 95% (non-condensing)
Range

Power Supply



1280W Redundant High-efficiency Digital Power Supplies w/ PMBus 1.2

- 1000W Output @ 100-140V, 8-12A, 50-60Hz

AC Input

- 1280W Output @ 180-240V, 6-8A, 50-60Hz

DC Output

- 1000W: +12V/83A; +5Vsb/4A
- 1280W: +12V/106.7A, +5Vsb/4A

Certification



Platinum Certified
[[Test Report](#)]

Regulatory (Power Supply)



- USA - UL listed
- Canada - CUL listed
- Germany - TUV Certified
- EN 60950/IEC 60950-Compliant
- CB Report
- CCC Certification

Power Supply Safety / EMC

Strona firmowa produktu:

[https://www.superstorage.pl/supermicro-superchassis-sc216be26-r1k28wb-2u-24xsff-red-psu-p-2307.ht
ml](https://www.superstorage.pl/supermicro-superchassis-sc216be26-r1k28wb-2u-24xsff-red-psu-p-2307.html)

