Supermicro SuperChassis SC216E26-R1200LPB 2U 24xSFF RED PSU

Kod producenta: CSE-216E26-R1200LPB

Chassis Form Factor	Rack 2U
# of 2.5 hot-swap bays	24
Power Supply	Redundant
PSU Wattage	1200W
PSU Certification	80+ Gold
Uwagi	Dual Expander SAS2 Backplane

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-216E26-R1200LPB	• SuperChassis 216E26-R1200LPB (**Black**)

Form Factor

2U chassis support for motherboard size
- 13.68" x 13", E-ATX and ATX

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Width	• 17.2" (437mm)
Height	• 3.5" (89mm)
Depth	• 24.8" (630mm)
Packaging	• 26.5" (W) x 10.5" (H) x 38" (L)
Weight	• Net Weight: 35 lbs (15.9kg) • Gross Weight: 57 lbs (25.9kg)
Available Color	Black

Expansion Slots

• 7x low-profile expansion slots

Drive Bays

Hot-swap	24x 2.5" SAS / SATA Hot-swap drive trays SAS or enterprise SATA HDD only recommended

Backplane

SAS2 dual Expander Backplane, features:
• Scalability through cascading
• 6Gb SAS2/SATA3 HDD support
• Inband SES-2 Enclosure Management
• Redundancy support through SAS drive only
• Single input/output SFF 8087 connectors

Front Panel

Buttons	• Power On/Off button • System Reset button
LEDs	• Power LED • Hard drive activity LED • 2x Network activity LEDs • System Overheat LED • Power fail LED

Motherboard (for CSE-216E26-R1200LPB)

H8DG6	H8DG6-F
H8DGi	H8DGi-F
X8DA6	X8DAE
X8DTH-i	X8DTH-iF
X8DTL-6	

System Cooling

Fans	3x 80mm 7000 RPM hot-swap PWM fans

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature Range	• 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range	• -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range	• 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range	• 5% - 95% (non-condensing)

Power Supply

Redundant 1200W high-efficiency power supply with PMBus

AC Input	• 1000W Output @ 100-140V, 11.5-8A, 50-60Hz • 1200W Output @ 180-240V, 8-5.5A, 50-60Hz
DC Output	• 1000W: +12V/83A; +5Vsb/4A • 1200W: +12V/100A; +5Vsb/4A
DC Output with PDB	• +5V: 50 Amp • +3.3V: 30 Amp • -12V: 0.6 Amp
Certification	**Gold Certified** **[Test Report]**

Regulatory (Power Supply)

Power Supply Safety / EMC	• USA - UL listed • Canada - CUL listed • Germany - TUV Certified • EN 60950/IEC 60950-Compliant • CB Report • CCC Certification

Strona firmowa produktu:
https://www.superstorage.pl/supermicro-superchassis-sc216e26-r1200lpb-2u-24xsff-red-psu-p-2308.html