

Supermicro SuperChassis SC216BE26-R920LPB 2U 24xSFF RED PSU

Kod producenta: CSE-216BE26-R920LPB



Chassis Form Factor	Rack 2U
# of 2.5 hot-swap bays	24
Power Supply	Redundant
PSU Wattage	920W
PSU Certification	80+ Platinum
Uwagi	Dual Expander SAS2 Backplane

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs



CSE-216BE26-R920LPB • SuperChassis 216BE26-R920LPB (Black)

Form Factor



2U chassis support for motherboard size
- 13.68" x 13", E-ATX and ATX

Processor Support



Supports dual, single Intel® / AMD processors

Dimensions



Width • 17.2" (437mm)
Height • 3.5" (89mm)
Depth • 24.8" (630mm)
Packaging • 26.5" (W) x 10.5" (H) x 38" (L)
Weight • Net Weight: 35 lbs (15.9kg)
• Gross Weight: 57 lbs (25.9kg)

Available Color Black

Expansion Slots



• 7x low-profile expansion slots

Drive Bays



Hot-swap 24x 2.5" SAS / SATA Hot-swap drive trays
SAS or enterprise SATA HDD only recommended

Backplane



SAS2 Expander Backplane, features:
• Scalability through cascading
• 6Gb SAS2/SATA3 HDD support
• Inband SES-2 Enclosure Management
• Single input/output SFF 8087 connectors

Front Panel



Buttons • Power On/Off button
• System Reset button

LEDs • Power LED
• Hard drive activity LED
• 2x Network activity LEDs
• System Overheat LED
• Power fail LED



Motherboard (for CSE-216BE26-R920LPB)



[X9DAi](#)
[X9DB3-TPF](#)
[X9DBi-TPF](#)
[X9DR3-LN4F+](#)
[X9DRD-7LN4F-JBOD](#)
[X9DRH-7F](#)
[X9DRH-iF](#)
[X9DRH-iTF](#)
[X9DRi-LN4F+](#)
[X9DB3-F](#)
[X9DBi-F](#)
[X9DR3-F](#)
[X9DRD-7LN4F](#)
[X9DRD-EF](#)
[X9DRH-7TF](#)
[X9DRH-iF-NV](#)
[X9DRi-F](#)



System Cooling



Fans 3x 80mm 7000 RPM hot-swap PWM fans

System Monitoring



Chassis intrusion switch



Operating Environment (System)



Operating
Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range
Non-Operating
Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range
Operating
Relative Humidity • 8% ~ 90% (non-condensing)
Range
Non-Operating
Relative Humidity • 5% - 95% (non-condensing)
Range

Power Supply

920W Redundant High-Efficiency Power Supplies w/ Power Distributor, PMBus 1.2, I²C, and PFC
AC Input • 100-240 V, 50-60 Hz, 11-4.5 Amp
DC Output • +5V standby: 4A
• +12V: 75A
• +5V: 45A
With Power Distributor • +3.3V: 24A
• -12V: 0.6A

Certification **Platinum Certified**
[[Test Report](#)]

Regulatory (Power Supply)



Power Supply Safety / EMC • USA - UL listed
• Canada - CUL listed
• Germany - TUV Certified
• EN 60950/IEC 60950-Compliant
• CB Report

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc216be26-r920lpb-2u-24xsff-red-psu-p-2316.html>