

Supermicro SuperChassis SC823TQ-653LPB 2U 6xLFF FIX PSU

Kod producenta: CSE-823TQ-653LPB



Chassis Form Factor	Rack 2U
# of 3.5 hot-swap bays	6
Power Supply	Fixed
PSU Wattage	650W
PSU Certification	80+ Gold

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs	Motherboard (for CSE-823TQ-653LPB)	
CSE-823TQ-653LPB • SuperChassis 823TQ-653LPB (Black)		
Form Factor		
2U chassis support for max. motherboard size - 12" x 13" E-ATX and 12" x 10" ATX		
Processor Support		
Supports dual, single Intel® / AMD processors		
Dimensions		
Height	3.5" (89mm)	
Width	16.8" (426mm)	
Depth	25.6" (650mm)	
Gross Weight	53 lbs (24.0kg)	
Available Colors	Black	
Expansion Slots		
• 7x low-profile full-length expansion slots		
Drive Bays		
Hot-swap	6x 3.5" SAS / SATA Hot-swap drive trays SAS or enterprise SATA HDD only recommended	
Peripheral Bay(s)	1x 5.25" full-height peripheral bay	
SAS / SATA Backplane		
1x 2U SAS / SATA backplane		
Peripheral Drives		
DVD-ROM	Slim DVD-ROM drive (optional)	
Front Panel		
Buttons	• Power On/Off button • System Reset Button • 2 Network Activity LEDs	
LEDs	• HDD activity LED • Power Status LED • System Information LED	
Ports	2x USB Ports (optional)	
	H8SCM	H8SCM-F
	X10DRi	X10DRi-T
	X10DRL-C	X10DRL-CT
	X10DRL-i	X10DRL-iT
	X10DRL-LN4	X10SL7-F
	X10SLA-F	X10SLH-F
	X10SLL+-F	X10SLL-F
	X10SLL-S	X10SLL-SF
	X10SLM+-F	X10SLM+-LN4F
	X10SLM-F	X10SRH-CF
	X10SRH-CLN4F	X10SRi-F
	X10SRL-F	X1SSA-F
	X9DBL-3	X9DBL-3F
	X9DBL-i	X9DBL-iF
	X9DRD-iF	X9DRD-LF
	X9DRL-3F	X9DRL-7F
	X9DRL-EF	X9DRL-iF
	X9SRE	X9SRE-3F
	X9SRE-F	X9SRH-7F
	X9SRH-7TF	X9SRL-F
	Server(s) for SC823TQ-653LPB	
	6028R-TT	6028R-T
	6027B-TLF	
	System Cooling	
	Fans	4x 8cm (7000 RPM) hot-swap PWM cooling fan
	System Monitoring	
	Chassis intrusion switch	
	Operating Environment (System)	
	Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F) Range	
	Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F) Range	
	Operating Relative Humidity • 8% ~ 90% (non-condensing) Range	
	Non-Operating Relative Humidity • 5% - 95% (non-condensing) Range	
	Power Supply	
	650W AC-DC High Efficiency Power Supply	
	AC Input • 100 - 140V, 8-5.2A 180-240V 4.2-3.1A, 50-60Hz	
	+5V • 30 Amp	
	+5V standby • 4 Amp	
	+12V • 100-140Vac 49Amp 180-240Vac 54Amp	
	-12V • 0.5 Amp	
	+3.3V • 25 Amp	
	Certification	 Gold Certified
	Regulatory (Power Supply)	
	Power Supply Safety / EMC • USA - UL listed, FCC • Canada - CUL listed • Germany - TUV Certified • Europe/CE Mark • EN 60950/IEC 60950-Compliant • CCC Certification	

Strona firmowa produktu:
<https://www.superstorage.pl/supermicro-superchassis-sc823tq-653lpb-2u-6xlf-fx-psu-p-2345.html>