

Supermicro SuperChassis SC745TQ-R1200B Tower/4U 8xLFF RED PSU

Kod producenta: CSE-745TQ-R1200B



Chassis Form Factor	Tower/4U
# of 3.5 hot-swap bays	8
Power Supply	Redundant
PSU Wattage	1200W
PSU Certification	80+ Gold

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-745TQ-R1200B • SuperChassis 745TQ-R1200B (Black)

Form Factor

Tower / 4U chassis support for max. motherboard size - 13.68" x 13" (34.7cm x 33cm), ATX, E-ATX

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

- Height • 17.8" (452mm)
- Width • 7.0" (178mm)
- Depth • 25.5" (648mm)
- Gross Weight • 58 lbs (26.3kg)
- Available Color • Black
- Package • 24.6" x 14" x 31.3"

Expansion Slots

7x PCI expansion slots

Drive Bays

- Hot-swap • 8x 3.5" Hot-swap SAS/SATA Drive Bays
- SAS or enterprise SATA HDD only recommended
- Peripheral Bay(s) • 2x 5.25" Peripheral Drive Bay
- 1x 5.25" Bay For Floppy Drive

SAS / SATA Backplane

SAS / SATA Hard Drive Backplane with SES2

Front Panel

- Buttons • Power On/Off button
- System Reset button
- Power LED
- Hard drive activity LED
- LEDs • 2x Network activity LEDs
- System Overheat LED
- Power Fail LED
- Ports • 2x USB Ports

Motherboard (for CSE-745TQ-R1200B)

- [X8DAH+](#)
- [X8DTN+](#)
- [X8DTN+-F-LR](#)
- [X9DA7](#)
- [X9DAi](#)
- [X9DRH-7TF](#)
- [X9DRH-iF-NV](#)
- [X8DAH+-F](#)
- [X8DTN+-F](#)
- [X8DTN+-LR](#)
- [X9DAE](#)
- [X9DRH-7F](#)
- [X9DRH-iF](#)
- [X9DRH-iTF](#)

System Cooling

- 3x 5000 RPM Hot-swap PWM Cooling Fans
- Fans • 2x 5000 RPM Hot-swap Rear Exhaust PWM Fans

System Monitoring

Chassis intrusion switch

Operating Environment (System)

- Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)
- Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)
- Operating Relative Humidity Range • 8% ~ 90% (non-condensing)
- Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

Power Supply

Redundant 1200W high-efficiency power supply with PMBus

- AC Input • 1000W Output @ 100-140V, 11.5-8A, 50-60Hz
- 1200W Output @ 180-240V, 8-5.5A, 50-60Hz
- DC Output • 1000W: +12V/83A; +5Vsb/4A
- 1200W: +12V/100A; +5Vsb/4A
- DC Output with PDB • +5V: 50 Amp
- +3.3V: 30 Amp
- -12V: 0.6 Amp

Certification



Gold Certified
[[Test Report](#)]

Regulatory (Power Supply)

- Power Supply Safety / EMC • USA - UL listed, FCC
- Canada - CUL listed
- China - CCC Mark
- Europe/CE Mark
- EN 60950/IEC 60950-Compliant
- Germany - TUV Certified

Strona firmowa produktu:
<https://www.superstorage.pl/supermicro-superchassis-sc745tq-r1200b-tower4u-8xlf-red-psu-p-2382.html>

