

# Supermicro SuperChassis SC842TQ-865B 4U 5xLFF FIX PSU

Kod producenta: CSE-842TQ-865B



|                        |         |
|------------------------|---------|
| Chassis Form Factor    | Rack 4U |
| # of 3.5 hot-swap bays | 5       |
| Power Supply           | Fixed   |
| PSU Wattage            | 865W    |
| PSU Certification      | 80+     |

*Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:*

| Product SKUs                                                                                                     |                                                                                     | Motherboard (for CSE-842TQ-865B ) |  |
|------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------|--|
| CSE-842TQ-865B • SuperChassis 842TQ-865B (Black)                                                                 |                                                                                     |                                   |  |
| Form Factor                                                                                                      |                                                                                     |                                   |  |
| Industrial Short-Depth 4U Rackmount supports E-ATX, ATX, Micro ATX motherboards; max. motherboard size 12" x 13" |                                                                                     |                                   |  |
| Processor Support                                                                                                |                                                                                     |                                   |  |
| Supports dual, single Intel® / AMD processors                                                                    |                                                                                     |                                   |  |
| Dimensions                                                                                                       |                                                                                     |                                   |  |
| Height                                                                                                           | • 7.0" (178mm)                                                                      |                                   |  |
| Width                                                                                                            | • 17.2" (437mm)                                                                     |                                   |  |
| Depth                                                                                                            | • 20.5" (521mm)                                                                     |                                   |  |
| Packaging                                                                                                        | • 26.4" (W) x 13.8" (H) x 31.5" (D)                                                 |                                   |  |
| Gross Weight                                                                                                     | 670mm (W) x 350mm (H) x 800mm (D)                                                   |                                   |  |
| Available Colors                                                                                                 | • Black                                                                             |                                   |  |
| Expansion Slots                                                                                                  |                                                                                     |                                   |  |
| 7x Tool-less Full-height, Full-length PCI Expansion Slots                                                        |                                                                                     |                                   |  |
| Drive Bays                                                                                                       |                                                                                     |                                   |  |
| Hot-swap                                                                                                         | • 5x 3.5" (8x 2.5" optional kits; SAS/SATA Hot-swap Drive Bays)                     |                                   |  |
|                                                                                                                  | • SAS or enterprise SATA HDD only recommended                                       |                                   |  |
| Peripheral Bay(s)                                                                                                | • 3x 5.25" Peripheral Drive Bays                                                    |                                   |  |
|                                                                                                                  | • 1x Slim DVD-ROM (optional) Drive Bay                                              |                                   |  |
| SAS / SATA Backplane                                                                                             |                                                                                     |                                   |  |
| SAS / SATA Hard Drive Backplane                                                                                  |                                                                                     |                                   |  |
| Front Panel                                                                                                      |                                                                                     |                                   |  |
| Buttons                                                                                                          | • Power On/Off button                                                               |                                   |  |
|                                                                                                                  | • System Reset button                                                               |                                   |  |
| LEDs                                                                                                             | • Power LED                                                                         |                                   |  |
|                                                                                                                  | • Hard drive activity LED                                                           |                                   |  |
|                                                                                                                  | • 2x Network activity LEDs                                                          |                                   |  |
|                                                                                                                  | • System Overheat LED                                                               |                                   |  |
|                                                                                                                  | • Power Fail LED                                                                    |                                   |  |
| Ports                                                                                                            | • 2x USB 2.0 Ports                                                                  |                                   |  |
| System Cooling                                                                                                   |                                                                                     |                                   |  |
| Fans                                                                                                             | fan                                                                                 |                                   |  |
| (Hot-plug)                                                                                                       | • 1x Front Intake 9cm PWM cooling fan                                               |                                   |  |
|                                                                                                                  | • 2x Rear 8cm PWM cooling fans                                                      |                                   |  |
| System Monitoring                                                                                                |                                                                                     |                                   |  |
| Chassis intrusion switch                                                                                         |                                                                                     |                                   |  |
| Operating Environment (System)                                                                                   |                                                                                     |                                   |  |
| Operating Temperature                                                                                            |                                                                                     |                                   |  |
|                                                                                                                  | • 5°C ~ 35°C (41°F ~ 95°F)                                                          |                                   |  |
| Range                                                                                                            |                                                                                     |                                   |  |
| Non-Operating Temperature                                                                                        |                                                                                     |                                   |  |
|                                                                                                                  | • -40°C ~ 60°C (-40°F ~ 140°F)                                                      |                                   |  |
| Range                                                                                                            |                                                                                     |                                   |  |
| Operating Relative Humidity                                                                                      |                                                                                     |                                   |  |
|                                                                                                                  | • 8% ~ 90% (non-condensing)                                                         |                                   |  |
| Range                                                                                                            |                                                                                     |                                   |  |
| Non-Operating Relative Humidity                                                                                  |                                                                                     |                                   |  |
|                                                                                                                  | • 5% - 95% (non-condensing)                                                         |                                   |  |
| Range                                                                                                            |                                                                                     |                                   |  |
| Power Supply                                                                                                     |                                                                                     |                                   |  |
| 865W AC power supply (cooling-redundant) w/ PFC                                                                  |                                                                                     |                                   |  |
| AC Voltage                                                                                                       |                                                                                     |                                   |  |
|                                                                                                                  | • 100 - 240V, 50-60Hz, 12-6 Amp                                                     |                                   |  |
| +5V standby                                                                                                      |                                                                                     |                                   |  |
|                                                                                                                  | • 6.5 Amp                                                                           |                                   |  |
| +12V                                                                                                             |                                                                                     |                                   |  |
|                                                                                                                  | • 70 Amp                                                                            |                                   |  |
| +5V                                                                                                              |                                                                                     |                                   |  |
|                                                                                                                  | • 30 Amp                                                                            |                                   |  |
| +3.3V                                                                                                            |                                                                                     |                                   |  |
|                                                                                                                  | • 30 Amp                                                                            |                                   |  |
| -12V                                                                                                             |                                                                                     |                                   |  |
|                                                                                                                  | • 1 Amp                                                                             |                                   |  |
| Certification                                                                                                    |                                                                                     |                                   |  |
|                                                                                                                  |  |                                   |  |
|                                                                                                                  | <a href="#">Certified</a>                                                           |                                   |  |
| Regulatory (Power Supply)                                                                                        |                                                                                     |                                   |  |
|                                                                                                                  | • USA - UL listed, FCC                                                              |                                   |  |
|                                                                                                                  | • Canada - CUL listed                                                               |                                   |  |
| Power Supply                                                                                                     | • Germany - TUV Certified                                                           |                                   |  |
| Safety / EMC                                                                                                     | • Europe/CE Mark                                                                    |                                   |  |
|                                                                                                                  | • EN 60950/IEC 60950-Compliant                                                      |                                   |  |

Strona firmowa produktu:  
<https://www.superstorage.pl/supermicro-superchassis-sc842tq-865b-4u-5x1ff-fix-psu-p-2397.html>