

Supermicro SuperChassis SC846XE2C-R1K23B 4U 24xLFF RED PSU

Kod producenta: CSE-846XE2C-R1K23B



Chassis Form Factor	Rack 4U
# of 3.5 hot-swap bays	24
Power Supply	Redundant
PSU Wattage	1200W
PSU Certification	80+ Titanium
Uwagi	Dual Expander SAS2 Backplane

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-846XE2C-R1K23B • SuperChassis
846XE2C-R1K23B (Black)

Form Factor

4U chassis for motherboard support size of 13.68" x 13" E-ATX, 12" x 10" ATX and and 15.2" x 13.2"

Processor Support

Dual and Single Intel® and AMD processors

Dimensions

- Height • 7" (178mm)
- Width • 17.2" (437mm)
- Depth • 29" (736mm)
- Packaging • 28" (W) x 18"(H) 42" (L)
- Gross Weight • 75 lb (34.02 kg)
- Available Colors • black

Expansion Slots

13 full-height & full-length expansion slot(s) 11 full height expansion slot(s)

Peripheral Drives

- 2 x Optional 3.5" internal fixed drive bay
- 2 x Optional 2.5" hot-swap drive bay
- 4 x Optional 2.5" internal fixed drive bay

Drive Bays

Hot-swap 24 x 3.5" hot-swap SAS/SATA drive bay with SES3

Front Panel

- Buttons**
 - Power On/Off button
 - System Reset Button
 - 2 Network Activity LEDs
 - Fan Fail/System Over Heat LED
- LEDs**
 - HDD activity LED
 - Power Status LED
 - Power Fail LED

Motherboard (for CSE-846XE2C-R1K23B)

[X10DRX](#)

[X9DRX+-F](#)

System Cooling

- Fans
 - 4x 8cm hot-swap redundant PWM cooling fans
 - 1x 8cm hot-swap exhaust fans & air shroud

System Monitoring

Chassis intrusion switch

Operating Environment (System)

- Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)
- Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)
- Operating Relative Humidity Range • 8% ~ 90% (non-condensing)
- Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

Power Supply

- Redundant 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL360xH40mm
 - 1000W Output @ 100-127V, 12-15A, 50-60Hz
 - 1200W Output @ 200-240V, 7-8.5A, 50-60Hz
- AC Input
 - 1000W: +12V/83A; +5Vsb/4A
 - 1200W: +12V/100A, +5Vsb/4A
- DC Output

Certification



Titanium Certified
[\[Test Report \]](#)

Regulatory (Power Supply)

- Power Supply Safety / EMC
 - USA - UL listed, FCC
 - Canada - CUL listed
 - Germany - TUV Certified
 - Europe/CE Mark
 - EN 60950/IEC 60950-Compliant

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc846xe2c-r1k23b-4u-24xlff-red-psu-p-2426.html>