

Supermicro SuperChassis SC732i-865B Mid-Tower 4xLFF FIX PSU

Kod producenta: CSE-732i-865B



Chassis Form Factor	Mid-Tower
# of 3.5 fixed bays	4
Power Supply	Fixed
PSU Wattage	865W
PSU Certification	80+

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKU	Motherboard (for CSE-732i-865B)	
CSE-732i-865B • SuperChassis 732i-865B (Black)		
Form Factor	X10DRH-CT	X10DRH-I
Mid-Tower & Workstation chassis support for max. motherboard size - 12" x 13" E-ATX	X10DRH-iT	X10DRi
Processor Support	X10DRi-T	X10SL7-F
Supports dual, single Intel® / AMD processors	X10SLA-F	X10SLH-F
Dimensions	X10SLL+-F	X10SLL-F
Width • 7.6" (193 mm)	X10SLL-S	X10SLL-SF
Height • 16.7" (424 mm)	X10SLM+-F	X10SLM+-LN4F
Depth • 20.68" (525.3 mm)	X10SLM-F	X10SLQ
Packaging • 21.38" (W) x 11.97" (H) x 25.28" (D)	X10SLQ-L	X10SLX-F
543mm (W) x 304mm (H) x 642mm (D)	X11SSA-F	X11SSQ
Weight • 30 lbs (13.6 kg)	X11SSQ-L	X8DTL-3
Available Colors • Black	X8DTL-3F	X8DTL-6
Expansion Slots	X8DTL-6F	X8DTL-I
7x Full-height, Full-length I/O expansion slots	X8DTL-IF	X9SCV-Q
Drive Bays	System Cooling	
Internal • 4x 3.5" SAS/SATA HDD Bays (90° rotatable drive cage)	Fans • 1x 12cm (1850rpm) rear exhaust fan	
Peripheral Bay • 2x 5.25" peripheral drive bays	• 1x 12cm (1850rpm) front cooling fan (opt.)	
• 1x 3.5" peripheral drive bay	• Optimized Cooling Technology at 21dB Whisper-Quiet Operation	
Front Panel	Operating Environment (System)	
Buttons • Power On/Off button	Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)	
LEDs • Hard drive activity LED	Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)	
• Network activity LED	Operating Relative Humidity Range • 8% ~ 90% (non-condensing)	
• System Overheat LED	Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)	
Ports • 2x Front USB 2.0 ports	Power Supply	
	865W AC power supply (cooling-redundant) w/ PFC	
	AC Voltage • 100 - 240V, 50-60Hz, 12-6 Amp	
	+5V standby • 6.5 Amp	
	+12V • 70 Amp	
	+5V • 30 Amp	
	+3.3V • 30 Amp	
	-12V • 1 Amp	
	Certification	 Certified
	Regulatory (Power Supply)	
	Power Supply Safety / EMC • USA - UL listed, FCC	
	• Canada - CUL listed	
	• Germany - TUV Certified	
	• Europe/CE Mark	
	• EN 60950/IEC 60950-Compliant	
	• CCC Certified	

Strona firmowa produktu:
<https://www.superstorage.pl/supermicro-superchassis-sc732i-865b-mid-tower-4x1ff-fix-psu-p-2435.html>