

Supermicro SuperChassis SC732D4F-500B Mid-Tower 4xLFF FIX PSU

Kod producenta: CSE-732D4F-500B



Chassis Form Factor	Mid-Tower
# of 3.5 fixed bays	4
Power Supply	Fixed
PSU Wattage	500W
PSU Certification	80+ Bronze

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKU
CSE-732D4F-500B • SuperChassis 732D4F-500B (Black)

Form Factor
Mid-Tower chassis support for motherboard sizes - 12" x 13" E-ATX, 12" x 10" ATX, and 9.6" x 9.6" Micro-ATX

Processor Support
Supports dual, single Intel® / AMD processors

Dimensions
Width • 7.6" (193 mm)
Height • 16.7" (424 mm)
Depth • 20.68" (525.3 mm)
Packaging • 21.38" (W) x 11.97" (H) x 25.28" (D)
Weight 543mm (W) x 304mm (H) x 642mm (D)
Available Colors • 30 lbs (13.6 kg)
Colors • Black

Expansion Slots
7x Full-height, Full-length I/O expansion slots

Drive Bays
Internal • 4x 3.5" SAS/SATA HDD Bays (90° rotatable drive cage)
Peripheral Bay • SAS or enterprise SATA HDD only recommended
• 2x 5.25" peripheral drive bays
• 1x 3.5" peripheral drive bay

Front Panel
Buttons • Power On/Off button
• Power status LED
LEDs • Hard drive activity LED
• Network activity LED
• System Overheat LED
Ports • 2x Front USB 3.0 ports
• 2x Front USB 2.0 ports
• 2x Front 1394 ports
• 2x Front HD/AC97 Audio ports

Motherboard (for CSE-732D4F-500B)

[C7B75](#) [C7Z87](#)
[C7Z87-OCE](#) [X10SAE](#)
[X10SAT](#) [X10SLQ](#)
[X10SLQ-L](#) [X11SSQ](#)
[X11SSQ-L](#) [X9SCV-Q](#)
[X9SRA](#)

Server(s) for SC732D4F-500B

[5038A-iL](#) [7037A-iL](#)

System Cooling
• 1x 12cm (1850rpm) rear exhaust fan
• 1x 12cm (1850rpm) front cooling fan (opt.)
• Optimized Cooling Technology at 21dB Whisper-Quiet Operation

Operating Environment (System)
Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range • 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

Power Supply
500W AC power supply w/ PFC
AC Voltage • 100 - 240V, 50-60Hz, 7-3.5 Amp
+5V • 20 Amp
+5V standby • 3 Amp
+12V1 • 17 Amp
+12V2 • 17 Amp
+12V3 • 17 Amp
+12V4 • 18 Amp
-12V • 0.5 Amp
+3.3V • 15 Amp

Certification 
Bronze Certified
[\[Test Report \]](#)

Regulatory (Power Supply)
Power Supply Safety / EMC • USA - UL listed, FCC
• Canada - CUL listed
• Germany - TUV Certified
• Europe/CE Mark
• EN 60950/IEC 60950-Compliant
• CCC Certified

Strona firmowa produktu:
[https://www.superstorage.pl/supermicro-superchassis-sc732d4f-500b-mid-tower-4x1ff-fix-psu-p-2438.ht](https://www.superstorage.pl/supermicro-superchassis-sc732d4f-500b-mid-tower-4x1ff-fix-psu-p-2438.html)
[ml](#)