

Supermicro SuperChassis SC732D4F-865B Mid-Tower 4xLFF FIX PSU

Kod producenta: CSE-732D4F-865B



Chassis Form Factor	Mid-Tower
# of 3.5 fixed bays	4
Power Supply	Fixed
PSU Wattage	865W
PSU Certification	80+

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKU

CSE-732D4F-865B • SuperChassis 732D4F-865B (Black)

Form Factor

Mid-Tower chassis support for motherboard sizes - 12" x 13" E-ATX, 12" x 10" ATX, and 9.6" x 9.6" Micro-ATX

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

- | | |
|------------------|---|
| Width | • 7.6" (193 mm) |
| Height | • 16.7" (424 mm) |
| Depth | • 20.68" (525.3 mm) |
| Packaging | • 21.38" (W) x 11.97" (H) x 25.28" (D)
543mm (W) x 304mm (H) x 642mm (D) |
| Weight | • 30 lbs (13.6 kg) |
| Available Colors | • Black |

Expansion Slots

7x Full-height, Full-length I/O expansion slots

Drive Bays

- | | |
|----------------|---|
| Internal | • 4x 3.5" SAS/SATA HDD Bays (90° rotatable drive cage)
• SAS or enterprise SATA HDD only recommended |
| Peripheral Bay | • 2x 5.25" peripheral drive bays
• 1x 3.5" peripheral drive bay |

Front Panel

- | | |
|---------|---|
| Buttons | • Power On/Off button
• Power status LED |
| LEDs | • Hard drive activity LED
• Network activity LED
• System Overheat LED |
| Ports | • 2x Front USB 3.0 ports
• 2x Front USB 2.0 ports
• 2x Front 1394 ports
• 2x Front HD/AC97 Audio ports |

Motherboard (for CSE-732D4F-865B)

- | | |
|-------------------------|--------------------------|
| C7B75 | C7Z87 |
| X10SAE | X10SAT |
| X10SLQ | X10SLQ-L |
| X11SSQ | X11SSQ-L |
| X9SCV-Q | |

System Cooling

- | | |
|------|--|
| Fans | • 1x 12cm (1850rpm) rear exhaust fan
• 1x 12cm (1850rpm) front cooling fan (opt.)
• Optimized Cooling Technology at 21dB Whisper-Quiet Operation |
|------|--|

Operating Environment (System)

- | | |
|---------------------------------------|--------------------------------|
| Operating Temperature Range | • 5°C ~ 35°C (41°F ~ 95°F) |
| Non-Operating Temperature Range | • -40°C ~ 60°C (-40°F ~ 140°F) |
| Operating Relative Humidity Range | • 8% ~ 90% (non-condensing) |
| Non-Operating Relative Humidity Range | • 5% - 95% (non-condensing) |

Power Supply

- 865W AC power supply (cooling-redundant) w/ PFC
- | | |
|-------------|---------------------------------|
| AC Voltage | • 100 - 240V, 50-60Hz, 12-6 Amp |
| +5V standby | • 6.5 Amp |
| +12V | • 70 Amp |
| +5V | • 30 Amp |
| +3.3V | • 30 Amp |
| -12V | • 1 Amp |

Certification



[Certified](#)

Regulatory (Power Supply)

- | | |
|---------------------------|---|
| Power Supply Safety / EMC | • USA - UL listed, FCC
• Canada - CUL listed
• Germany - TUV Certified
• Europe/CE Mark
• EN 60950/IEC 60950-Compliant
• CCC Certified |
|---------------------------|---|

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc732d4f-865b-mid-tower-4xlff-fix-psu-p-2439.html>