

Supermicro SuperChassis SC732D4F-903B Mid-Tower 4xLFF FIX PSU

Part number: CSE-732D4F-903B



SC732D4F front I/O:
2x USB 3.0 ports,
2x USB 2.0 ports,
2x 1394 ports,
2x HD/AC97 Audio ports



Chassis Form Factor	Mid-Tower
# of 3.5 fixed bays	4
Power Supply	Fixed
PSU Wattage	900W
PSU Certification	80+ Gold

Product SKU

CSE-732D4F-903B • SuperChassis 732D4F-903B (Black)

Form Factor

Mid-Tower chassis support for motherboard sizes - 12" x 13" E-ATX, 12" x 10" ATX, and 9.6" x 9.6" Micro-ATX

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Width	• 7.6" (193 mm)
Height	• 16.7" (424 mm)
Depth	• 20.68" (525.3 mm)
Packaging	• 21.38" (W) x 11.97" (H) x 25.28" (D) 543mm (W) x 304mm (H) x 642mm (D)
Weight	• 30 lbs (13.6 kg)
Available Colors	• Black

Expansion Slots

7x Full-height, Full-length I/O expansion slots

Drive Bays

Internal	• 4x 3.5" SAS/SATA HDD Bays (90° rotatable drive cage) • SAS or enterprise SATA HDD only recommended
Peripheral Bay	• 2x 5.25" peripheral drive bays • 1x 3.5" peripheral drive bay

Front Panel

Buttons	• Power On/Off button • Power status LED
LEDs	• Hard drive activity LED • Network activity LED • System Information LED
Ports	• 2x Front USB 3.0 ports • 2x Front USB 2.0 ports • 2x Front HD/AC97 Audio ports • 2x Front Firewire 1394 ports

Motherboard (for CSE-732D4F-903B)

C7B75	C7Z87
X10DRH-CT	X10DRH-I
X10DRH-iT	X10DRi
X10DRi-T	X10DRL-C
X10DRL-CT	X10DRL-i
X10DRL-iT	X10SAE
X10SAT	X10SLO
X10SLQ-L	X10SRH-CF
X10SRL-F	X11SSQ
X11SSQ-L	X9DA7
X9DAE	X9SRA

Server(s) for SC732D4F-903B

[7037A-i](#)

System Cooling

Fans	• 1x 12cm (1850rpm) rear exhaust fan • 1x 12cm (1850rpm) front cooling fan (opt.) • Optimized Cooling Technology at 21dB Whisper-Quiet Operation
------	--

Operating Environment (System)

Operating Temperature Range	• 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range	• -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range	• 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range	• 5% - 95% (non-condensing)

Power Supply

900W AC multi output power supply	
AC Voltage	• 100-240 V, 50-60 Hz, 10-6 Amp
+5V Standby	• 3 Amp
+12V1	• 25 Amp
+12V2	• 25 Amp
+12V3	• 25 Amp
+12V4	• 25 Amp
+5V	• 25 Amp
+3.3V	• 25 Amp
-12V	• 0.5 Amp

Certification



Gold Level

Note:	• Max. continuous combined load on +3.3V and +5V output shall not exceed 155W. • Max. continuous combined load on +12V1, +12V2, +12V3 and +12V4 output shall not exceed 860W.
-------	--

Regulatory (Power Supply)

Power Supply Safety / EMC	• USA - UL listed, FCC • Canada - CUL listed • Germany - TUV Certified • Europe/CE Mark • EN 60950/IEC 60950-Compliant • CE Certified
---------------------------	--

Visit us for more info:

<https://www.superstorage.pl/supermicro-superchassis-sc732d4f-903b-mid-tower-4xlff-fix-psu-p-2442.html>