

Supermicro SuperChassis SC514-R400W 1U 2xSFF RED PSU

Kod producenta: CSE-514-R400W



Chassis Form Factor	Rack 1U
# of 2.5 fixed bays	2
Power Supply	Redundant
PSU Wattage	400W

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs	Motherboard (for CSE-514-R400W)	
CSE-514-R400W	• SuperChassis 514-R400W (No Paint)	
Form Factor	X10DRW-E	X10DRW-ET
1U chassis for motherboard support size of Proprietary 12.3" x 13", Proprietary 8.15" x 13.05"	X10DRW-N	X10DRW-NT
	X10SRW-F	X11SSW-F
	X9SRW-F	X9SRW-F
Processor Support	Server(s) for SC514-R400W	
Supports dual, single Intel® / AMD processors	1028R-WMR	1028R-WMRT
Dimensions	System Cooling	
Height	4x 40x56mm PWM fan	
Width	2x fans for AOC cooling	
Depth		
Gross Weight	Operating Environment (System)	
Packaging	Operating	
Available Color	Temperature	
	• 5°C ~ 35°C (41°F ~ 95°F)	
Expansion Slots	Range	
2 full height expansion slot(s)	Non-Operating	
1 low-profile expansion slot(s)	Temperature	
	• -40°C ~ 60°C (-40°F ~ 140°F)	
Drive Bays	Range	
Internal Bay	Operating	
• Up to 2x 2.5" fixed with bracket	Relative	
• SAS or enterprise SATA HDD only recommended	Humidity	
	• 8% ~ 90% (non-condensing)	
Front Panel	Range	
Buttons	Non-Operating	
• Power On/Off button	Relative	
• System Reset Button	Humidity	
• 2 Network Activity LEDs	• 5% - 95% (non-condensing)	
• Fan Fail/System Over Heat LED	Range	
• HDD activity LED	Power Supply	
• Power Status LED	400W SuperCompact Short-depth AC-DC high-efficiency power supply with PMBus and I2C	
	AC Voltage	
	• 400W: 100-240 V, 50-60 Hz, 6-3 Amp	
	DC Output	
	• 3 Amp	
	+5V standby	
	DC Output	
	• 3 Amp	
	+5V standby	
	With Power	
	• +5V: 25 Amp	
	• +3.3V: 25 Amp	
	Distributor	
	• -12V: 0.6 Amp	
	Regulatory (Power Supply)	
	• USA - UL listed, FCC	
	• Canada - CUL listed	
	• Germany - TUV Certified	
	• Europe/CE Mark	
	• EN 60950, IEC 60950-1, EN 60950-2	
	Power Supply Safety / EMC	

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc514-r400w-1u-2xsff-red-psu-p-2457.html>