

Supermicro SuperChassis SC515-505 1U 4xSFF 1xLFF FIX PSU

Kod producenta: CSE-515-505



Chassis Form Factor	Rack 1U
# of 2.5 fixed bays	4
# of 3.5 fixed bays	1
Power Supply	Fixed
PSU Wattage	500W
PSU Certification	80+ Platinum

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs	Motherboard (for CSE-515-505)	
CSE-515-505 • SuperChassis 515-505 (No Paint)		
Form Factor	X10SRM-F	X10SRM-TF
1U chassis for motherboard support size of Proprietary 12.3" x 13", Proprietary 8.15" x 13.05"	X11SSZ-F	X11SSZ-QF
	X11SSZ-TLN4F	
Processor Support	System Cooling	
Supports dual, single Intel® / AMD processors	Fans	4x 40x56mm PWM fan 2x fans for AOC cooling
Dimensions	System Monitoring	
Height 1.7" (43mm)	Chassis intrusion switch	
Width 17.2" (437mm)		
Depth 16.9" (429mm)	Operating Environment (System)	
Gross Weight 16 lb (7.26 kg)	Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)	
Packaging 27" (W) x 8"(H) 24" (L)	Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)	
Available Color No Paint	Operating Relative Humidity Range • 8% ~ 90% (non-condensing)	
Expansion Slots	Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)	
2 full height expansion slot(s)	Power Supply	
Drive Bays	500W High-Efficiency Power Supply w/PMBus 1.2, I ² C, and PFC	
Internal Bay • Up to Optional 4x 2.5" fixed with bracket • Up to 1x 3.5" fixed drive bay	AC Input • 100-240V, 50-60Hz, 6.6A max • +3.3V: 12A • +5V: 15A DC Output • +5V standby: 3A • +12V: 41A • -12V: 0.2A	
Front Panel	Certification  Platinum Certified	
Buttons • Power On/Off button • System Reset Button	Regulatory (Power Supply)	
LEDs • 2 Network Activity LEDs • Fan Fail/System Over Heat LED • HDD activity LED • Power Status LED	• USA - UL listed, FCC • Canada - CUL listed Power Supply Safety / EMC • Germany - TUV Certified • Europe/CE Mark • EN 60950 / IEC 60950 Compliant	

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc515-505-1u-4xsff-1xlff-fix-psu-p-2460.html>