Supermicro SuperChassis SC515-350 1U 2xSFF 1xLFF FIX PSU

Part number: CSE-515-350

Chassis Form Factor	Rack 1U
# of 2.5 fixed bays	2
# of 3.5 fixed bays	1
Power Supply	Fixed
PSU Wattage	350W
PSU Certification	80+ Platinum

Product SKUs

CSE-515-350 • SuperChassis 515-350 (No Paint)

Form Factor

1U - Support STD and WIO MB

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height	1.7" (43mm)
Width	17.2" (437mm)
Depth	16.9" (429mm)
Gross Weight	16 lb (7.26 kg)
Packaging	27'' (W) x 8''(H) 24'' (L)
Available Color	No Paint

Expansion Slots

Up to **Without Universal I/O (UIO) Card:**
2 full height expansion slot(s)

Drive Bays

Internal Bay	• Up to Optional 4x 2.5" fixed with bracket • Up to 1x 3.5" fixed drive bay

Front Panel

Buttons	• Power On/Off button • System Reset Button
LEDs	• 2 Network Activity LEDs • Fan Fail/System Over Heat LED • HDD activity LED • Power Status LED

Motherboard (for CSE-515-350)

X10SRM-F X10SRM-TF

System Cooling

Fans	4x 40x56mm PWM fan 2x fans for AOC cooling

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature Range	• 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range	• -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range	• 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range	• 5% - 95% (non-condensing)

Power Supply

350W AC power supply w/ PFC

AC Voltage	• 100-240 V, 50-60 Hz, 4.2-1.8 Amp
+5V	• Max.: 15 Amp • Min.: 0.2 Amp
+5V standby	• Max.: 3 Amp • Min.: 0 Amp
+12V	• Max.: 29 Amp • Min.: 0.5 Amp
-12V	• Max.: 0.2 Amp • Min.: 0 Amp
+3.3V	• Max.: 12 Amp • Min.: 0.2 Amp
Certification	**Platinum Level Certified** **[Test Report]**

Regulatory (Power Supply)

Power Supply Safety / EMC	• USA - UL listed, FCC • Canada - CUL listed • Germany - TUV Certified • Europe/CE Mark • EN 60950/IEC 60950-Compliant