

Supermicro SuperChassis SC733TQ-500B Mid-Tower 4xLFF FIX PSU

Kod producenta: CSE-733TQ-500B



Chassis Form Factor	Mid-Tower
# of 3.5 hot-swap bays	4
Power Supply	Fixed
PSU Wattage	560W
PSU Certification	80+ Bronze

Product SKUs

CSE-733TQ-500B • SuperChassis 733TQ-500B (Black)

Form Factor

Mid-Tower & Workstation chassis support for max. motherboard size - 12" x 13" E-ATX

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

- Height • 16.8" (427 mm)
- Width • 7" (178 mm)
- Depth • 20.9" (531 mm)
- Weight • 39 lbs (17.7 kg)
- Available Colors • Black

Expansion Slots

7x Full-height, Full-length expansion slots

Drive Bays

- Hot-swap • 4x 3.5" SAS / SATA hot-swap drive bays
- Peripheral Bay • SAS or enterprise SATA HDD only recommended
- Peripheral Bay • 2x 5.25" peripheral drive bay
- Bay • 1x 3.5" bay

SAS / SATA Backplane

4 x 3.5" SAS / SATA Backplane with SES2

Front Panel

- Buttons • Power On/Off button
- Buttons • System Reset button
- Buttons • Power LED
- LEDs • Hard drive activity LED
- LEDs • Network activity LED
- LEDs • System Overheat LED
- Ports • 2x Front side USB ports (USB 2.0 ready)

Motherboard (for CSE-733TQ-500B)

- | | |
|---------------------------|------------------------------|
| C7B75 | C7Z87 |
| C7Z87-OCE | X10SAE |
| X10SAT | X10SL7-F |
| X10SLA-F | X10SLH-F |
| X10SLL+-F | X10SLL-F |
| X10SLL-S | X10SLL-SF |
| X10SLM+-F | X10SLM+-LN4F |
| X10SLM-F | X10SLX-F |
| X9SCI-LN4 | X9SCL |
| X9SCL+-F | X9SCL-F |
| X9SCM | X9SCM-F |
| X9SCM-iiF | X9SRH-7F |
| X9SRH-7TF | X9SRi |
| X9SRi-3F | X9SRi-F |

System Cooling

- Fans • 1x 92mm Front Thermal Fan

Operating Environment (System)

- Operating Temperature Range • 10° - 35°C (50° - 95°F)
- Non-Operating Temperature Range • -40° - 70°C (-40° - 158°F)
- Humidity Range • 8 - 90% non-condensing
- Non-Operating Humidity Range • 5 - 95% non-condensing

Power Supply

- 500W AC power supply w/ PFC
- AC Voltage • 100 - 240V, 50-60Hz, 7-3.5 Amp
- +5V • 20 Amp
- +5V standby • 3 Amp
- +12V1 • 17 Amp
- +12V2 • 17 Amp
- +12V3 • 17 Amp
- +12V4 • 18 Amp
- 12V • 0.5 Amp
- +3.3V • 15 Amp



Certification

Bronze Certified
[[Test Report](#)]

Regulatory (Power Supply)

- | | |
|---------------------------|--|
| Power Supply Safety / EMC | <ul style="list-style-type: none">• USA - UL listed, FCC• Canada - CUL listed• Germany - TUV Certified• Europe/CE Mark• EN 60950/IEC 60950-Compliant• CCC Certified |
|---------------------------|--|

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc733tq-500b-mid-tower-4xlff-fix-psu-p-2479.html>

