

# Supermicro MBD-X10SLL+-F, Single SKT, Intel C222 Chipset, SATA, 2xGbE, IPMI Bulk

Part number: MBD-X10SLL+-F-B



|                     |  |
|---------------------|--|
| Form Factor         | uATX   |
| Dimensions          | 9.6" x 9.6"  |
| CPU Socket          | LGA 1150 (Socket H3)   |
| # of CPU sockets    | 1  |
| Supported CPU's     | Intel Xeon E3-1200v3<br>Intel Xeon E3-1200v4   |
| Chipset             | Intel C222 Lynx Point  |
| Memory Type         | DDR3 ECC UDIMM   |
| Memory Speed        | 1600 MHz<br>1333 MHz   |
| # of DIMM's         | 4  |
| Max Memory Size     | 32 GB  |
| Integrated GPU      | Aspeed AST2400   |
| # of PCIe x8 3.0    | 2  |
| # of PCIe x4 2.0    | 1  |
| # of USB Ports      | 1 x USB 3.0 (rear)<br>1 x USB 3.0 Type A<br>4 x USB 2.0 (rear)<br>2 x USB 2.0 (header) |
| # of SATA Ports     | 6  |
| # of SATA DOM power | 1  |
| Storage Controllers | 2 x AHCI iSATA 6Gb/s<br>4 x AHCI iSATA 3Gb/s   |
| Integrated RAID     | 0,1,5,10   |
| # of Serial Ports   | 1 x Fast UART 16550 (rear)<br>1 x Fast UART 16550 (header)                             |
| # of 1GbE Ports     | 2 x RJ45   |
| Network Controllers | Intel i210 Dual Port Gigabit Ethernet  |
| Integrated BMC      | IPMI 2.0<br>KVM-over-LAN<br>Virtual Media over LAN<br>IPMI Dedicated RJ45 PHY          |
| BMC chip            | Aspeed AST2400   |
| TPM                 | 1 x TPM 1.2 20-pin Header  |

