

Supermicro MBD-X10SLM+-LN4F, Single SKT, Intel C224 Chipset, SATA, 4xGbE, IPMI Bulk

Kod producenta: MBD-X10SLM+-LN4F-B



Form Factor	uATX
Dimensions	9.6" x 9.6"
CPU Socket	LGA 1150 (Socket H3)
# of CPU sockets	1
Supported CPU's	Intel Xeon E3-1200v3 Intel Xeon E3-1200v4
Chipset	Intel C224 Lynx Point
Memory Type	DDR3 ECC UDIMM
Memory Speed	1600 MHz 1333 MHz
# of DIMM's	4
Max Memory Size	32 GB
Integrated GPU	Aspeed AST2400
# of PCIe x16 3.0	1
# of PCIe x2 2.0	1
# of USB Ports	2 x USB 3.0 (rear) 1 x USB 3.0 (header) 1 x USB 3.0 Type A 2 x USB 2.0 (rear) 4 x USB 2.0 (header)
# of SATA Ports	6
# of SATA DOM power	1
Storage Controllers	4 x AHCI iSATA 6Gb/s 2 x AHCI iSATA 3Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports	1 x Fast UART 16550 (rear) 1 x Fast UART 16550 (header)
# of 1GbE Ports	4 x RJ45
Network Controllers	Intel i210 Quad Port Gigabit Ethernet
Integrated BMC	IPMI 2.0 KVM-over-LAN Virtual Media over LAN IPMI Dedicated RJ45 PHY
BMC chip	Aspeed AST2400
TPM	1 x TPM 1.2 20-pin Header
Uwagi	PCI-Express Slots Configuration: 1x PCI-E 3.0 x16 slot 1x PCI-E 2.0 x2 (in x8) slot

Product SKUs		Chassis (Optimized for X10SLM+LN4F)	
MBD-X10SLM+LN4F • X10SLM+LN4F (Bulk Pack)		• SC113MT0-R400CB • SC113MT0-330CB-P • SC811T0-441B • SC542E-3500B • SC812T-441B • SC813MT0-R400CB-P • SC813MT0-350CB-P • SC813MT0-441CB • SC2131T-600L-PB • SC825MT0-B700L-PB • SC842T0-653L-PB • SC813L-550L-PB	
Physical Stats		1U Chassis:	
Form Factor • microATX		2U Chassis:	
Dimensions • 9.6" x 9.6", (24.4cm x 24.4 cm)		3U Chassis:	
Processor/Cache		Mid/Mini Tower Chassis:	
CPU		4U / Tower Chassis:	
System Memory		SuperServer(s) with X10SLM+LN4F Model(s) • SYS-500B-MTN-LN4F	
Memory Capacity		Expansion Slots	
Memory Type		PCI-Express	
Memory Sizes		System BIOS	
Memory Voltage		BIOS Type	
Error Detection		BIOS Features	
On-Board Devices		Management	
Chipset		Software	
SATA		Power Configurations	
IPMI		PC Health Monitoring	
Network Controllers		Voltage	
VGA		FAN	
Input / Output		Temperature	
Serial ATA		LED	
LAN		Other Features	
USB		Operating Environment	
VGA		Operating Temperature Range	
Serial Port / Header		Non-Operating Temperature Range	
DOM		Operating Relative Humidity Range	
TPM		Non-Operating Relative Humidity Range	

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-mbd-x10slm-ln4f-single-skt-intel-c224-chipset-sata-4xgbe-ipmi-bulk-p-2565.html>