

# Supermicro MBD-X10SRA-F, Single SKT, Intel C612 Chipset, SATA, 2xGbE, IPMI Bulk

Part number: MBD-X10SRA-F-B



Form Factor	ATX
Dimensions	12" x 9.6"
CPU Socket	LGA 2011 (Socket R3)
# of CPU sockets	1
Supported CPU's	Intel Xeon E5-2600v3 Intel Xeon E5-1600v3
Chipset	Intel C612 Wellsburg
Memory Type	DDR3 ECC LRDIMM DDR3 ECC RDIMM DDR3 ECC UDIMM DDR3 non-ECC UDIMM
Memory Speed	2133 MHz 1866 MHz 1600 MHz 1333 MHz
# of DIMM's	8
Max Memory Size	512 GB
Integrated GPU	Aspeed AST2400
# of PCIe x16 3.0	4
# of PCIe x4 2.0	2
# of USB Ports	6 x USB 3.0 (rear) 2 x USB 3.0 (header)
# of SATA Ports	10
Storage Controllers	6 x AHCI iSATA 6Gb/s 4 x sSATA 6Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports	1 x Fast UART 16550 (header)
# of 1GbE Ports	2 x RJ45
Network Controllers	Intel i210-AT Dual Port Gigabit Ethernet
Integrated BMC	IPMI 2.0 KVM-over-LAN
BMC chip	Aspeed AST2400
TPM	1 x TPM 1.2 20-pin Header

