

Supermicro MBD-X9DRD-iT+, Dual SKT, Intel C602 Chipset, SATA, 2x10GbE, IPMI Bulk

Part number: MBD-X9DRD-iT+-B



Form Factor	EE-ATX
Dimensions	13.7" x 13"
CPU Socket	LGA 2011 (Socket R)
# of CPU sockets	2
Supported CPU's	Intel Xeon E5-2600v2 Intel Xeon E5-2600
Chipset	Intel C602 Patsburg
Memory Type	DDR3 ECC LRDIMM DDR3 ECC RDIMM DDR3 ECC UDIMM DDR3 non-ECC UDIMM
Memory Speed	1866 MHz 1600 MHz 1333 MHz 1066 MHz 800 MHz
# of DIMM's	24
Max Memory Size	1536 GB
Integrated GPU	Nuvoton WPCM450
# of USB Ports	4 x USB 2.0 (rear) 2 x USB 2.0 (header) 1 x USB 2.0 Type A
# of SATA Ports	10
# of SATA DOM power	2
# of NVMe ports	2
Storage Controllers	2 x AHCI iSATA 6Gb/s 4 x AHCI iSATA 3Gb/s 4 x sSATA 3Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports	1 x Fast UART 16550 (rear)
# of 10GbE Ports	2 x Base-T
Network Controllers	Intel x540 Dual Port 10 Gigabit Base-T
Integrated BMC	IPMI 2.0 KVM-over-LAN Virtual Media over LAN IPMI Dedicated RJ45 PHY
BMC chip	Nuvoton WPCM450
TPM	1 x TPM 1.2 20-pin Header

Product SKUs	<input type="checkbox"/>	Chassis (Optimized for X9DRD-IT+)
<input type="checkbox"/> MBD-X9DRD-IT+ -0	<input type="checkbox"/>	U Chassis
<input type="checkbox"/> MBD-X9DRD-IT+ -B	<input type="checkbox"/>	<ul style="list-style-type: none"> • CSE-815TQ-600WB • To support the new generation Intel® Xeon® processor-based motherboards, Revision M chassis is recommended. Please talk to your sales representative for details.
Physical Stats	<input type="checkbox"/>	Important Chassis Notes
Form Factor	<input type="checkbox"/>	SuperServer(s) with X9DRD-IT+
Dimensions	<input type="checkbox"/>	Model(s)
Processor/Cache	<input type="checkbox"/>	<ul style="list-style-type: none"> • SYS-6017R-TDT+ • SYS-6027R-TDT+
CPU	<input type="checkbox"/>	Expansion Slots
Note	<input type="checkbox"/>	PCI-Express
Note	<input type="checkbox"/>	System BIOS
Cache	<input type="checkbox"/>	BIOS Type
System Bus	<input type="checkbox"/>	BIOS Features
System Memory	<input type="checkbox"/>	Management
Memory Capacity	<input type="checkbox"/>	Software
Memory Type	<input type="checkbox"/>	Power Configurations
DIMM Sizes	<input type="checkbox"/>	PC Health Monitoring
Memory Voltage	<input type="checkbox"/>	Voltage
Error Detection	<input type="checkbox"/>	FAN
On-Board Devices	<input type="checkbox"/>	Temperature
Chipset	<input type="checkbox"/>	LED
AHCI SATA	<input type="checkbox"/>	Other Features
SCU SATA	<input type="checkbox"/>	Operating Environment
IPMI	<input type="checkbox"/>	Operating Temperature Range
Network Controllers	<input type="checkbox"/>	Non-Operating Temperature Range
Video	<input type="checkbox"/>	Operating Relative Humidity Range
Input / Output	<input type="checkbox"/>	Non-Operating Relative Humidity Range
SATA	<input type="checkbox"/>	
LAN	<input type="checkbox"/>	
USB	<input type="checkbox"/>	
Video	<input type="checkbox"/>	
Serial Port / Header	<input type="checkbox"/>	
SATA DOM	<input type="checkbox"/>	
TPM	<input type="checkbox"/>	

Visit us for more info:

<https://www.superstorage.pl/supermicro-mbd-x9drd-it-dual-skt-intel-c602-chipset-sata-2x10gbe-ipmi-bulk-p-2614.html>